

3. SLEEVES IN BEARING AND MASONRY WALLS, FLOORS, AND PARTITIONS SHALL BE STANDARD WEIGHT STEEL PIPE FINISHED WITH SMOOTH EDGES. FOR OTHER THAN MASONRY PARTITIONS, THROUGH SUSPENDED CEILINGS, OR FOR CONCEALED VERTICAL PIPING, SLEEVES SHALL BE NO. 22 U.S.G. GALVANIZED STEEL MINIMUM.

SECTION 26 05 53 - IDENTIFICATION FOR ELECTRICAL SYSTEMS

1. TRANSFORMERS ARE GENERALLY INCLUDED IN THE IFS SWITCHGEAR. IF NOT, TRANSFORMER SHALL BE PAD MOUNTED OR SHALL BE SECURELY MOUNTED FROM THE BUILDING STRUCTURE, REINFORCED WALLS OR AS

SECTION 25 25 15 - ENCASED SWITCHES AND CIRCUIT BREAKERS

SECTION 26 51 00 - INTERIOR LIGHTING

END OF SECTION 28 51 00

FLA	FULL LOAD AMPS	RT	RAIN TIGHT
		RTU	ROOF TOP UNIT
1	GROUND		

FOR
ES
LD
GFIII
22
V
E:
UEC

Westerville, Ohio 43081
phone: 614.899.1620

ELECTRICAL

SPECIFICATIONS

E011

A
