



ANNOTATION SYMBOL LEGEND	NO SCALE	D 09.12.12
	05N-A0004-D00-NOTE	

<b>SYMBOL</b>	<b>DESCRIPTION</b>	<b>SYMBOL</b>	<b>DESCRIPTION</b>	<b>SYMBOL</b>	<b>DESCRIPTION</b>
	NON-DIRECTIONAL RECESSED DOWNLIGHT		ILLUMINATED EXIT SIGNAGE		SECURITY DOME (DUMMY DRONE)
	RECESSED DOWNLIGHT W/ EMERGENCY BACKUP		DIRECTIONAL ILLUMINATED EXIT SIGNAGE		ANALOG SECURITY CAMERAS
	DIRECTION RECESSED LIGHT		WALL SCONCE FIXTURES (SYMBOL WILL VARY)		IP SECURITY CAMERAS
	LIGHTING TRACK AND HEADS		PENDANT FIXTURES (SYMBOL WILL VARY)		TRAFFIC COUNTER
	SINGLE TUBE FLUORESCENT LIGHT FIXTURE		STAGGERED VERTICAL FLUORESCENT LIGHTS		PAGING SYSTEM CEILING SENSOR
	DOUBLE TUBE FLUORESCENT LIGHT FIXTURE		RECESSED MULTI-LIGHT FIXTURE		SUPPLY AIR DIFFUSER
	DOUBLE TUBE FLUORESCENT W/ EMERGENCY BACKUP		WALL MOUNTED NEON OR LED SIGN		RETURN AIR DIFFUSER
	CHAIN TUBE FLUORESCENT CHAIN HUNG		SPEAKER - WHITE FINISH		TOILET EXHAUST FAN
	DOUBLE TUBE FLUORESCENT CHAIN HUNG W/ EMERGENCY BACKUP		SUBWOOFER - WHITE FINISH		LINEAR SLOT DIFFUSER
	X4 SURFACE MNT'D FLUORESCENT		SUBWOOFER - BLACK FINISH		ACCESS PANEL (SYMBOL MAY VARY SLIGHTLY)
	X4 SURFACE MNT'D FLUORESCENT W/ EM BACKUP		SPEAKER - BLACK FINISH		DUPLEX FLOOR OUTLET
	RECESSED PARABOLIC FLUORESCENT FIXTURE		SUBWOOFER - BLACK FINISH		DUPLEX FLOOR OUTLET WITH DATA
	RECESSED PARABOLIC FLUORESCENT FIXTURE W/ EMERGENCY BACKUP		FAUX SPEAKER SCREEN - WHITE FINISH		QUAD FLOOR OUTLET
	FRAGRANCE DEVICE		FAUX SPEAKER SCREEN - BLACK FINISH		STORE INDICATED QTY OF FIXTURES (END-END) X NO. OF COLUMNS
	MOUNTING OPTIONS: FDI=CLG, FDX=TRACK, FDP=HALL, FDB=COL, FDS=X		SECURITY MONITOR		NOTE:
					FOR ALL OTHER ELECTRICAL, FIRE PROTECTION, MECHANICAL, AND PLUMBING SYMBOLS REFER TO THE DRAWINGS.

REFLECTED CEILING PLAN GENERAL NOTES	NO SCALE	C 09.12.13
	05N-A0004-C00-NOTE	

ABV	ABOVE	GA	GAUGE	(R)	RELOCATED
ACT	ACCOUSTICAL CEILING TILE	G.C.	GENERAL CONTRACTOR	RD	RADIUS
A.F.F.	ABOVE FINISH FLOOR	GYP BD	GYP/SUB BOARD	REQD	REQUIRED
ALUM	ALUMINUM	HDF	HIGH DENSITY FIBERBOARD	(REF)	REFERENCE
A.W.I.	AMERICAN WOOD INSTITUTE	HGT	HEIGHT	RG5	REGISTERS
ASTM	AMERICAN SOCIETY FOR TESTING AND MATERIALS	HORIZ	HORIZONTAL	R.O.	ROUGH OPENING
		H.M.	HOLLOW METAL	S.C.	SOLID CORE
		HOUR	HOUR	SECT	SECTION
BBW	BATH AND BODY WORKS	HVAC	HEATING, VENTILATION, AIR	SHT	SHEET
BD	BOARD		CONDITIONING	SIMLAR	SIMILAR
BLRG	BLOCKING	I.D.	INSIDE DIMENSION	SPL	SPECIAL
B.O.	BOTTOM OF	IFS	INTEGRATED FACILITY SYSTEM	SQ	SQUARE
BS	BRA SALON	IN	INCHES	SFL	SQUARE FEET
BW	BACKWARP	INCAND	INCANDESCENT	S.S.	STAINLESS STEEL
		INT	INTERIOR	SSPA	STEEL STUD MANUFACTURERS ASSOC.
CBPB	CEMENT BONDED PARTICLE BOARD			STC	STON TRANSMISSION COEFFICIENT
C./C.	CENTERLINE	LAV	LAVATORY	STL	STEEL
CLG	CEILING	L.L.	LANDLORD	STRUCT	STRUCTURE
C.H.	CONSTRUCTION MANAGER	L.L.	LEASE LINE	SURF	SURFACE
C.O.	CORNER	L.L.S	LIMITED LOGISTIC SERVICES		
CONC	CONCRETE	L504C	LIMITED STORE DESIGN #		
CONSTR	CONSTRUCTION	LTS	CONSTRUCTION	TEMP	TEMPERATURE
C.T.F.	CUT TO FIT		LIMITED TECHNOLOGY SERVICES	THRU	THROUGH
CN	CASHPARK	MAX	MAXIMUM	T.O.	TOP OF
C/C	CENTER TO CENTER	MDF	MEDIUM DENSITY FIBERBOARD	TRANS	TRANSITION
		MECH	MECHANICAL	TYP	TYPICAL
DIAG	DIAGONAL	MFG	MANUFACTURER	U.L.	UNDERWRITERS LABORATORIES
DIA.	DIAHETER	MISC	MISCELLANEOUS	U.N.O.	UNLESS NOTED OTHERWISE
		MIN	MINIMUM	U.O.N.	UNLESS OTHERWISE NOTED
E	EACH	MTL	MOUNTED	V.C.	VOLUME CONTROL
EFS	EXTERIOR INSULATION FINISH SYSTEM	MTL	METAL	VERT	VERTICAL
ELEV	ELEVATION	N/A	NOT APPLICABLE	V.I.F.	VERIFY IN FIELD
E.P.A.	ENVIRONMENTAL PROTECTION AGENCY	N/A	NOT IN CONTRACT	V.S.L	VICTORIA'S SECRET LINGERIE
EQ	EQUAL	N.P.	NEUTRAL PIER	V.S.V.	VICTORIA'S SECRET
(E)	EXISTING	(N)	NEW	W	WITH
EXT	EXTERIOR	N.T.S.	NOT TO SCALE	WD	WOOD
				W/O	WITHOUT
F.C.D.	FINISHED CABINET DIMENSION	O.C.	ON CENTER	W.I.C.	WOOD INSTITUTE COUNCIL
FD	FLOOR DRAIN	O.D.	OUTSIDE DIMENSION		
F.D.	FINISH DIMENSION	OPNG	OPENING		
F.H.	FLAT HEAD	OPNG	OPPOSITE		
FHSDS	FLAT HEAD SELF DRILLING SCREW	PKG	PACKAGE		
FIN	FINISH	PL	PLATE		
FL	FLOOR	PXG	PX/GLASS		
FLG	FLOORING	PLYWD	PLYWOOD		
FLUOR	FLUORESCENT	PREFN	PRE-FINISHED		
F.O.	FINISHED OPENING	PM	PROJECT MANAGER		
FR	FITTING ROOM	P.T.	PRESSURE TREATED		
F.R.P.	FIBERGLASS REINFORCED PANELS	QTY	QUANTITY		
F.R.T.	FIRE RESISTIVE TREATED				
FT	FEET				

- OR WALLCOVERING FINISHES ONLY SHALL RECEIVE 5/8" GYP. BD.; SURFACES WHICH RECEIVE PANELING (I.E. LAMINATE, WOOD GRAIN, OR PRIMED) SHALL RECEIVE 1/4" GYP. BD. UNDER THE 3/8" PANEL TO CREATE AN OVERALL DIMENSION OF 5/8". REFER TO PLANS FOR SPECIFIC FINISH LOCATIONS.
3. ALL ANGLED WALLS ARE TO BE 45° U.O.N. ON PLAN OR CONSTRUCTION DETAILS.
4. FLOOR LEVELING REQUIREMENTS, SALES AREA MAX. SLOPE OF 1/8"/10'-0", STOCKROOM (FOR FIXED SHELVING PAD, MAX. SLOPE 0.5% FOR MOBILE SHELVING, MAX. SLOPE 0.1%)
5. REFER TO MECHANICAL/STRUCTURAL DRAWINGS FOR H.V.A.C. EQUIPMENT SERVICE PLATFORM LOCATIONS (IF ANY), SPECIFICATIONS AND INSTALLATION NOTES AND DETAILS.
6. ALL CABINET ROUGH OPENINGS & FINISHED CABINET DIMENSIONS ARE CRITICAL DIMENSIONS. IF FIELD DIMENSION VARIES FROM THOSE SHOWN ON PLAN, LSD&C PROJECT MANAGER SHOULD BE NOTIFIED IMMEDIATELY.
7. SAW CUTTING MAY BE REQD FOR INSTALLATION OF SENSORIOMATIC EQUIPMENT. DASHED LINES INDICATE POSITION OF SENSORIOMATIC PADS / COILS AT ENTRANCE. OWNER'S VENDOR WILL TAP/ANTENNA LOCATIONS PRIOR TO SAW CUTTING. REFER TO ELECTRICAL DRAWINGS FOR SPECIFIC INSTALLATION DETAILS AND REQUIREMENTS. TYP. AT ALL ENTRANCES.
8. ALL G.C. SUPPLIED WOOD TRIM @ BLOCKING TO BE FREE FROM ANY KNOTS, DEFECTS, ETC., ONLY CLEAR FINISH GRADE BOARDS WILL BE ACCEPTED BY LSD&C PROJECT MANAGER.
9. G.C. TO PREPARE ALL SLABS AS NECESSARY FOR INSTALLATION OF FINISH FLOORING.
10. (REF) INDICATES A REFERENCE DIMENSION WHICH IS NOT CRITICAL AND MAY VARY IN THE FIELD. IF DIMENSION VARIES CONSIDERABLY MORE THAN NOTED ON DRAWINGS, NOTIFY THE LSD&C PROJECT MANAGER IMMEDIATELY.
11. ENGINEERED WOOD FLOORING LAYOUT TO START IN CENTER OF ROOM, TRANSITION, OR DISPLAY WINDOW WITH FULL BOARDS. TYP. AS INDICATED BY HATCHED CIRCLE. NO PERIMETER BOARD SHOULD MEASURE LESS THAN HALF THE WIDTH OF ONE BOARD IN ANY DIRECTION. LAYOUT APPLIES TO ALL ROOMS, U.O.N.
12. TILE LAYOUT IN ROOMS TO START IN CENTER W/FULL TILE(S), OR AS INDICATED ON PLAN. NO PERIMETER TILE SHOULD MEASURE LESS THAN HALF THE WIDTH OF ONE TILE IN ANY DIRECTION. LAYOUT APPLIES TO ALL ROOMS, U.O.N.
13. TILE LAYOUT AT TRANSITION, PORTAL, OR DISPLAY TO START AS INDICATED ON PLAN W/ FULL TILE(S). NO PERIMETER TILE SHALL MEASURE LESS THAN HALF THE WIDTH OF A TILE IN ANY DIRECTION.
14. WHEREVER THE FLOOR FINISH CHANGES OR TERMINATES, ALIGN THE OUTSIDE EDGE OF THE FINISH W/ THE FACE OF THE BASE MATERIAL. NOTE THE FACE OF THE GYP. BD. - W/AL. FINISH. REFER TO CONSTRUCTION DETAILS FOR THE BASE MATERIAL THICKNESS AS THIS MAY VARY FROM ROOM TO ROOM.
15. ALL TILE GROUT JOINTS TO BE 1/16" WIDE U.O.N.
16. G.C. TO HOLD FLOOR TILES MIN. 1/4" - 3/8" AWAY FROM PERIMETER WALLS FOR EXPANSION CONTROL. THIS GAP SHALL BE COVERED BY WALL BASE.
17. WHEN TWO DISSIMILAR TILES MEET, THE GC SHALL USE THE GROUT OF THE LIGHTER TILE AT THE JOINT BETWEEN THE TWO. THIS IS TO PREVENT THE DARKER GROUT COLOR FROM STAINING THE LIGHTER TILE.

## ABREVIATIONS

FLOOR AND FINISH PLAN GENERAL NOTES	NO SCALE	A 09.12.13
	05N-A0004-A00-NOTE	