

GENERAL


- GC TO INFILL MALL FLOORING FROM LEASELINE TO FACE OF STOREFRONT AS REQUIRED. VERIFY AMOUNT IN FIELD
- GC TO INSTALL LANDLORD APPROVED WATERPROOF MEMBRANE UNDER FLOOR. FINISH MEMBRANE TO CONTINUE MIN. 4' UP ADJOINING WALLS
- FLOOR FINISH TO CONTINUE UNDERNEATH CASHWRAP AND BACKWRAP FIXTURES
- WHERE DISSIMILAR FLOOR FINISHES OR PATTERNS MEET, THEY SHALL TERMINATE AT THE FACE OF PLINTH; NOT AT FACE OF GYP. BD.
- WALKOFF MAT. G.C. TO PAINT SLAB BLACK BENEATH PRIOR TO INSTALLATION
- ANTI FATIGUE MAT PLACED ON TOP OF FLOOR FINISH.
- FLOORING TO RUN IN DIRECTION INDICATED IN PLAN. GC TO INSTALL VAPOR BARRIER AT ALL LOCATIONS. REFER TO SPECIFICATIONS SECTION 094422 FOR INSTALLATION INSTRUCTIONS.
- FRP WAINSCOT TO ONLY BE INSTALLED AT EXPOSED WALLS. DO NOT INSTALL BEHIND PERMANENT FIXTURES (I.E. SHELVING, LOCKERS, ELECTRICAL PANELS, ETC.)
- SLATWALL IS APPLIED AT THIS WALL. GC DOES NOT NEED TO PROVIDE PAINT OR FRP HERE. SEE A10.02 FOR EXTENT.
- ROTATE CARPET TILES ONE QUARTER TURN FROM ADJACENT TILE.
- SEE DETAIL D/A11.05 FOR WALLCOVERING ORIENTATION.

PINK

- PINK HEX TILE ENTRY FLOORING. CENTER PATTERN ON PORTAL OPENING WITH A HALF TILE ON LEASE LINE.
- NOT USED
- NOT USED
- NOT USED
- NOT USED
- NOT USED
- NOT USED

VSS

- TARGET INDICATES THE START POINT OF TILE PATTERN BASED ON CENTER OF A FULL TILE OR CENTER OF A GROUT JOINT. G.C. TO ENSURE ALIGNMENT OF GROUT JOINTS FOR TILES BETWEEN ROOMS AND TRANSITIONS AS SHOWN AND WHEN FEASIBLE, UNLESS OTHERWISE NOTED.
- GROUT JOINTS AT ROOMS TO EITHER SIDE OF THE GRAND HALL SHALL ALIGN WITH THE JOINTS IN THE GRAND HALL. THE JOINTS AT THE TRANSITION MAY NOT ALIGN.
- FLOORING PATTERN TO START AT CENTER OF TRANSITION ENSURING THAT PLANKS AT EDGES ARE GREATER THAN 1/2 OF A SINGLE PLANK.
- SET TILES ENSURING IDENTICAL PATTERN IS NOT PLACED ADJACENT TO EACH OTHER. REFER TO MANUFACTURER INSTRUCTIONS FOR EXAMPLES.



NOTE:  
FOR PAINTING TRIM, BASE, AND PRIMED MDF PANELS IN THE BRA SALON, FITTING ROOM AREA, PUBLIC HALLWAYS/ VESTIBULES, AND PUBLIC TOILET ROOMS, THE GC SHALL CREATE A LIGHT BRUSH STROKE EFFECT. THIS SHALL MATCH EXACTLY THE BRUSH FINISH THAT IS PROVIDED BY THE VENDOR ON THE FITTING ROOM DOOR LEAVES.

NOTE: (P-29 PAINT)  
FOR ALL PINK SALES AREA WALLS, WAINSCOT, TRIM, AND BASE PAINTING REFER TO SPECIFICATIONS SECTION 099000 SUBSECTION P FOR SPECIAL INSTRUCTIONS TO ACHIEVE THE REQUIRED FINISH

NOTE:  
G.C. TO APPLY PRIMER BEHIND PAINT STENCILS REFER TO SPECIFICATIONS SECTION 099000 SUBSECTION O FOR SPECIAL INSTRUCTIONS

REFER TO SHEET A00.03 FOR FINISH SCHEDULE