



ANNOTATION SYMBOL LEGEND

1. ELECTRICAL CONTRACTOR IS TO TILT THE LAMP IN ALL AIM-ABLE FIXTURES AT A 30 DEGREE ANGLE TOWARD HALL OR CLOSET PER DIRECTION FROM THE LSDMC PROJECT MANAGER PRIOR TO STORE OPENING - REFER TO "DIRECTION ARROWS" ON PLAN
2. IF MUSIC SPEAKERS NEED TO BE RELOCATED OTHER THAN WHAT IS SHOWN ON REFLECTED CLG. PLAN, THEN RELOCATE TO THE CLOSEST POSSIBLE TO GIVEN LOCATION. RELOCATE IN A SYMMETRICAL PATTERN IN RELATIONSHIP TO ADJACENT LIGHTS AND SPRINKLER HEADS
3. G.C. IS TO PROVIDE ACCESS PANELS AS REQUIRED BY LANDLORD TO GAIN ACCESS TO PULL BOXES, DAMPERS, VALVES, TEMPERATURE CONTROL. (COORDINATE LOCATIONS IN FIELD WITH LSDMC - LOCATE IN SYMMETRICAL PATTERN WITH LIGHTING LAYOUT) SEE ACCESS PANEL SPECIFICATIONS.
4. ALL DIMENSIONS SHOWN ON REFLECTED CEILING PLAN ARE TO FACE OF GYP DBL OR TO FACE OF FINISH U.O.N. SEE CONSTRUCTION DETAILS FOR CLARIFICATION.
5. NO COMBUSTIBLE MATERIALS OF ANY TYPE ALLOWED ABOVE FINISHED CEILING OR IN ANY OTHER CONCEALED OR NON SPRINKLED SPACE.
6. WHEN A LEDGE IS LOCATED ABOVE THE MANAGER'S OFFICE OR ABOVE THE LAVATORIES, G.C. IS RESPONSIBLE TO MAKE SURE THESE LEDGES ARE KEPT CLEAR OF ALL CONDUIT AND OTHER ITEMS THAT MAY RUN ABOVE. IF IT IS NECESSARY TO RUN CONDUIT OR OTHER ITEMS, HOLD THEM TIGHT TO FULL HEIGHT WALLS TO ALLOW USE OF LEDGE. SEE REFLECTED CEILING PLAN FOR EXTENT OF LEDGE.
7. ALL CEILING HEIGHTS ARE FROM THE TOP OF FINISH FLOOR TO UNDERSIDE OF FINISH CEILING
8. PROVIDE ADEQUATE CLEARANCES FOR FIXTURES, DUCTS, CEILINGS AND RELATED PERTINENT ITEMS NECESSARY TO MAINTAIN THE SPECIFIED HEIGHTS ABOVE FINISH FLOOR.
9. ALL EXIT SIGNS ARE TO BE CEILING MOUNTED U.O.N.

REFLECTED CEILING PLAN

GENERAL NOTES

REFLECTED CEILING PLAN GENERAL NOTES	NO SCALE	C 09.12.13
	05N-A0004-C00-NOTE	

1. ALL DIMENSIONS SHOWN ON CONSTRUCTION PLAN ARE TO FACE OF GYP BD OR TO FACE OF FINISH U.O.N. SEE CONSTRUCTION DETAILS FOR CLARIFICATION.
2. THE GYP. BD. / FINISH DIMENSION AT ALL SURFACES HAS BEEN MAINTAINED AT 5/8" THICK. SURFACES RECEIVING PAINT OR WALLCOVERING FINISHES ONLY SHALL RECEIVE 5/8" GYP. BD.; SURFACES WHICH RECEIVE PANELING (I.E. LAMINATE, WOOD GRAIN, OR PRIMED) SHALL RECEIVE 1/4" GYP. BD. UNDER THE 3/8" PANEL TO CREATE AN OVERALL DIMENSION OF 5/8". REFER TO PLANS FOR SPECIFIC FINISH LOCATIONS.
3. ALL ANGLED WALLS ARE TO BE 45° U.O.N. ON PLAN OR CONSTRUCTION DETAILS.
4. FLOOR LEVELING REQUIREMENTS, SALES AREA MAX. SLOPE OF 8'/10'-0", STOCKROOM (FOR FIXED SHELVING PAD, MAX. SLOPE 0.5% FOR MOBILE SHELVING, MAX. SLOPE 0.01%).
5. REFER TO MECHANICAL/STRUCTURAL DRAWINGS FOR H.V.A.C. EQUIPMENT SERVICE PLATFORM LOCATIONS (IF ANY), SPECIFICATIONS AND INSTALLATION NOTES AND DETAILS.
6. ALL CABINET ROOF OPENINGS & FINISHED CABINET DIMENSIONS ARE CRITICAL DIMENSIONS. IF FIELD DIMENSION VARIES FROM THOSE SHOWN ON PLAN, L5DC'S PROJECT MANAGER SHOULD BE NOTIFIED IMMEDIATELY.
7. SAW CUTTING MAY BE REQUIRED FOR INSTALLATION OF SENSORIMOTRIC EQUIPMENT. DASHED LINES INDICATE POSITION OF SENSORIMOTRIC PADS & COILS AT ENTRANCE. OWNER'S VENDOR WILL LAUNCH ANTENNA LOCATIONS PRIOR TO SAW CUTTING. REFER TO ELECTRICAL DRAWINGS FOR SPECIFIC INSTALLATION DETAILS AND REQUIREMENTS. TYP. AT ALL ENTRANCES.
8. ALL G.C. SUPPLIED WOOD TRIM & BLOCKING TO BE FREE FROM ANY KNOTS, DEFECTS, ETC., ONLY CLEAR FINISH GRADE BOARDS WILL BE ACCEPTED BY L5DC PROJECT MANAGER.
9. G.C. TO PREPARE ALL SLABS AS NECESSARY FOR INSTALLATION OF FINISH FLOORING.
10. (REF.) INDICATES A REFERENCE DIMENSION WHICH IS NOT CRITICAL, AND MAY VARY IN THE FIELD. IF DIMENSION VARIES CONSIDERABLY MORE THAN NOTED ON DRAWINGS, NOTIFY THE L5DC PROJECT MANAGER IMMEDIATELY.
11. ENGINEERED WOOD FLOORING LAYOUT TO START IN CENTER OF ROOM, TRANSITION, OR DISPLAY WINDOW WITH FULL BOARD. TYP. AS INDICATED BY HATCHED CIRCLE. NO PERIMETER BOARD SHOULD MEASURE LESS THAN HALF THE WIDTH OF ONE BOARD IN ANY DIRECTION. LAYOUT APPLIES TO ALL ROOMS, U.O.N.
12. TILE LAYOUT IN ROOMS TO START IN CENTER W/FULL TILE(S), OR AS INDICATED ON PLAN. NO PERIMETER TILE SHOULD MEASURE LESS THAN HALF THE WIDTH OF ONE TILE IN ANY DIRECTION. LAYOUT APPLIES TO ALL ROOMS, U.O.N.
13. TILE LAYOUT AT TRANSITION, PORTAL, OR DISPLAY TO START AS INDICATED ON PLAN w/ FULL TILE(S). NO PERIMETER TILE SHALL MEASURE LESS THAN HALF THE WIDTH OF A TILE IN ANY DIRECTION.
14. WHEREVER THE FLOOR FINISH CHANGES OR TERMINATES, ALIGN THE OUTSIDE EDGE OF THE FINISH w/ THE FACE OF THE BASE MATERIAL, NOT THE FACE OF THE GYP. BD. / WALL FINISH. REFER TO CONSTRUCTION DETAILS FOR THE BASE MATERIAL THICKNESS AS THIS MAY VARY FROM ROOM TO ROOM.
15. ALL TILE GROUT JOINTS TO BE 1/16" WIDE U.O.N.
16. G.C. TO HOLD FLOOR TILES MIN. 1/4" - 3/8" AWAY FROM PERIMETER WALLS FOR EXPANSION CONTROL. THIS GAP SHALL BE COVERED BY FLOOR TILES.
17. WHEN TWO DISSIMILAR TILES MEET, THE GC SHALL USE THE GROUT OF THE LIGHTER TILE AT THE JOINT BETWEEN THE TWO. THIS IS TO PREVENT THE DARKER GROUT COLOR FROM STAINING THE LIGHTER TILE.

FLOOR AND FINISH PLAN GENERAL NOTES

FLOOR AND FINISH PLAN GENERAL NOTES	NO SCALE	A 09.12.13
	05N-A0004-A00-NOTE	

DRAWING NUMBER:
A00.4