

311 ELM STREET
SUITE 600
CINCINNATI, OH 45202
513 241 3000
www.frch.com

1215 METRO PARKWAY
FT. MYERS, FL. 33966

Soma

STORE NO:
5062

PROJECT LOCATION:
MIROMAR OUTLETS
10801 CORKSCREW ROAD
ESTERO, FL 33928
SPACE #: 407

DESIGN TYPE:	
REVISIONS:	
REQUIRED BY:	DATE
_____	_____
_____	_____
_____	_____
_____	_____
_____	_____
INDICATES NO REVISION TO THIS SHEET	
DRAWN BY: LKM	
CHECKED BY: CMB	

ITE CONSTRUCTION GROUP
AKE JACKSON, TX
PHONE: 979-285-0712
NOTE: THESE PRINTS HAVE BEEN REDUCED
Y 50 PERCENT. SCALE WILL BE 50 PERCENT
F WHAT IS NOTED ON PLANS

DRAWING TITLE:
NON-SALES
DETAILS

DATE ISSUED:
06/06/2017

PROJECT NO:
034138.000

DRAWING NO:

A14.1

NOT USED

NOTE: TACTILE CHARACTERS ON SIGNS SHALL BE LOCATED 48 INCHES MINIMUM ABOVE THE FINISH FLOOR OR GROUND SURFACE, MEASURED FROM THE BASELINE OF THE LOWEST TACTILE CHARACTER AND 60 INCHES MAXIMUM ABOVE FINISH FLOOR OR GROUND SURFACE, MEASURED FROM THE BASELINE OF THE HIGHEST TACTILE CHARACTER.

M

$$6'' = 1'-0''$$

FINISH FLOOR, REFER
TO FINISH PLAN ———

G.C. TO CAULK ALL JOINTS
BETWEEN CORNER GUARD AND
GYP. BD. WITH NON-SHRINKING
PAINTABLE, FLEXIBLE, WHITE
LATEX CAULK

1/2" DIA. HOLE
IN BOTTOM CAP——

SECTION THRU TUBE 2

NOTE:
G.C. MUST PROVIDE AND ATTACH A LABEL (WITH CLEAR TAPE) STATING: THIS TUBE CONTAINS STORE DRAWINGS AND IS NOT TO BE REMOVED WITHOUT THE CONSENT OF THE STORE MANAGER.

NOTE:
ENTIRE ASSEMBLY IS CONSTRUCTED
BY G.C. IN FIELD. G.C. TO PAINT
BLOCKING **P-1A**

①

R	
---	--

L

6" = 1'-0"
-

N.T.S.

2X WOOD BLOCKING

SHIM AS REQD

1" x 4 7/8" MILLED HARDWOOD JAMB

1 3/8" X 1 3/8" HARDWOOD STOP

TAPE & MUD SMOOTH (TYP. WHERE WOOD OCCURS)

3 5/8" x 20 GA. MTL. STUDS

DISPLAY AREA

HOLLOW-CORE DOOR

1/4"

4 7/8"

1"

3 5/8" x 1 3/4" SOLID-CORE WOOD DOOR

HINGE - PROVIDE/SECURE TO CUSTOM-SIZED DOOR

5/8" GYP. BD. EACH SIDE OF 3 5/8" MTL. STUD FRAMING. PROVIDE TYPE "X" AT RATED PARTITIONS

WOOD CASING ON NON-SALES SIDE

5/8"

NOT USED

NON-SALES

NOT USED




Diagram illustrating the front panel of the unit. The front panel is shown with a large diagonal line across it, indicating it is not to be used. The text "NOT USED" is written across the panel. The front panel is labeled "FRONT PANEL" and "FRONT PANEL" (repeated). The front panel is shown with a large diagonal line across it, indicating it is not to be used.

CREW

MON

1/4"

$$3'' = 1'-0''$$

N.T.S.

4 7/8"

NESTED MTL. STUD HEADER

NON-SALES

7'-0" x 1 3/4"
SOLID-CORE WOOD DOOR

HARDWOOD DOOR FRAME

HOLLOW-CORE DOOR

5/8" GYP. BD. EACH SIDE OF
3 5/8" MTL. STUD FRAMING.
PROVIDE TYPE "X" AT
RATED PARTITION

DISPLAY AREA

NOT USED

Diagram illustrating the installation of a steel track on a floor. The diagram shows a cross-section of the floor and the track assembly. Key components and labels include:

- HILTI BOLT**: Points to the bolt securing the track to the floor.
- WASHER**: Points to the washer under the bolt head.
- END STOP**: Points to the stop at the end of the track.
- 1/4" X 5/8" STEEL INSERT**: Points to the insert used for alignment.
- HILTI SCREW 3/16" X 1 3/4"**: Points to the screw used to secure the track.
- ALUMINUM TRACK**: Points to the track being installed.
- STAGGERED BOLT JOINTS**: Points to the staggered bolt joints.
- FLOOR**: Points to the floor surface.
- EACH END, TYP. ALL TRACK**: Points to the end of the track.
- ALIGN STEEL TO ALUMINUM TRACK. USE 3/16" HILTI DRILL, DRILL 2 3/4" MIN. DEPTH IN FLOOR**: Points to the alignment instruction.

A large diagonal watermark reading "NOT USED" is overlaid on the diagram.

~~N~~

N.T.S.

$$1/2'' = 1'-0''$$

A14.1