



- (N) BEAUTY SHELF LIGHTING - SEE DETAIL L/A11.2
- (E) SECURITY SYSTEM MONITOR TO REMAIN
- (N) V55 FITTING ROOM MIRROR WALL SCONCE FIXTURE MOUNTED WITH CENTER AT 4'-9" A.F.F.
- (N) V55 FITTING ROOM PENDANT LIGHT FIXTURE - E.D. REFER TO DETAIL L/A11.2
- (N) V55 CASHWRAP PENDANT LIGHT FIXTURE - E.D. REFER TO DETAIL L/A11.2
- (N) RELOCATED MOUNTED NEON SIGNAGE - INSTALL WITH E.D. REFER TO DETAIL L/A11.2
- (N) BUILD LETTER PINE SIGNAGE AT BASE OF WALL OF HALLWAY - REFER TO DETAIL L/A11.2
- (N) PENDANT MOUNTED DRUM SHADE AND LIGHTING. REFER TO M/A11.2 AND ELECTRICAL DRAWINGS.

- (N) TRAFFIC COUNTER WITH BLACK FINISH.
- (N) TRAFFIC COUNTER WITH WHITE FINISH.
- (N) PENDANT MOUNTED DRUM SHADE AND LIGHTING. REFER TO M/A11.2 AND ELECTRICAL DRAWINGS.

- (N) TRANS #6 TRANS #7
- (N) TRANS #5 TRANS #12
- (N) TRANS #17 TRANS #15
- (N) TRANS #16 TRANS #14

- (N) V55 FITTING ROOM MIRROR WALL SCONCE FIXTURE MOUNTED WITH CENTER AT 4'-9" A.F.F.
- (N) V55 TRANSITION SCONCE FIXTURE MOUNTED TO BASE OF TRANSITION CLOSET AT BASE
- (N) V55 CASHWRAP SCONCES. REFER TO MEP DRAWINGS FOR POWER

- (R) SPEAKER GRILLE AND (R) SPEAKER. G.C. TO COORDINATE RECONNECTION TO EXISTING SYSTEM.
- (E) LIGHT FIXTURE TO REMAIN. G.C. TO REPLACE (E) TRIM HOUSING W/ (N) BLACK TRIM HOUSING.
- (N) EXIT SIGN. REFER TO ELECTRICAL DRAWINGS FOR MORE INFORMATION.

- (E) OR (R) SECURITY DOMES. G.C. TO PAINT TRIM TO MATCH CEILING COLOR [P-71R(N)]
- (E) OR (R) MECHANICAL DIFFUSER OR RETURN TO BE PAINTED TO MATCH CEILING COLOR [P-71R(N)]
- (E) OR (R) MECHANICAL DIFFUSER OR RETURN TO BE PAINTED TO MATCH CEILING COLOR [P-71R(N)]

- (E) OR (R) SECURITY DOMES. G.C. TO PAINT TRIM TO MATCH CEILING COLOR [P-71R(N)]
- (E) OR (R) MECHANICAL DIFFUSER OR RETURN TO BE PAINTED TO MATCH CEILING COLOR [P-71R(N)]
- (E) OR (R) MECHANICAL DIFFUSER OR RETURN TO BE PAINTED TO MATCH CEILING COLOR [P-71R(N)]

- (E) OR (R) SECURITY DOMES. G.C. TO PAINT TRIM TO MATCH CEILING COLOR [P-71R(N)]
- (E) OR (R) MECHANICAL DIFFUSER OR RETURN TO BE PAINTED TO MATCH CEILING COLOR [P-71R(N)]
- (E) OR (R) MECHANICAL DIFFUSER OR RETURN TO BE PAINTED TO MATCH CEILING COLOR [P-71R(N)]

REFLECTED LIGHTING PLAN KEYNOTES

1. ELECTRICAL CONTRACTOR IS TO TILT THE LAMP IN ALL AIMABLE FIXTURES AT A 30 DEGREE ANGLE TOWARD WALL OR CABINETS PER DIRECTION FROM THE LSCD. PROJECT MANAGER PRIOR TO STORE OPENING - REFER TO 'DIRECTION ARROWS' ON PLAN
2. G.C. IS TO PROVIDE ACCESS PANELS AS REQUIRED BY LANDLORD TO GAIN ACCESS TO PULL BOXES, DAMPERS, VALVES, TEMPERATURE CONTROL. (COORDINATE LOCATIONS IN FIELD WITH LSCD - LOCATE IN SYMMETRICAL PATTERN WITH LIGHTING LAYOUT) SEE ACCESS PANEL SPECIFICATIONS.
3. ALL DIMENSIONS SHOWN ON REFLECTED CEILING PLAN ARE TO FACE OF GYP. BD. OR TO FACE OF FINISH U.O.N. SEE CONSTRUCTION DETAILS FOR CLARIFICATION.
4. NO COMBUSTIBLE MATERIALS OF ANY TYPE ALLOWED ABOVE FINISHED CEILING OR IN ANY OTHER CONCEALED OR NON SPRINKLED SPACE.
5. PROVIDE ADEQUATE CLEARANCES FOR FIXTURES, DUCTS, CEILINGS AND RELATED PERTINENT ITEMS NECESSARY TO MAINTAIN THE SPECIFIED HEIGHTS ABOVE FINISH FLOOR.
6. ALL EXIT SIGNS ARE TO BE CEILING MOUNTED U.O.N.
7. ALL SPEAKERS AND SUBWOOFERS, MECHANICAL SUPPLY AND RETURN DIFFUSERS, SPRINKLER HEADS, EXIT LIGHTING, TRACK LIGHTING AND FIXTURE LIGHTING TO REMAIN. U.O.N. G.C. TO REPLACE AS NECESSARY.

REFLECTED LIGHTING PLAN GENERAL NOTES

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
(X)	NON-DIRECTIONAL RECESSED DOWNLIGHT	(X)	ILLUMINATED EXIT SIGNAGE	(SD)	SECURITY DOME (DUPPLY DRONE)
(X)	RECESSED DOWNLIGHT W/ EMERGENCY BACKUP	(X)	DIRECTIONAL ILLUMINATED EXIT SIGNAGE	(AN)	ANALOG SECURITY CAMERAS
(X)	DIRECTION RECESSED LIGHT	(X)	WALL SCONCE FIXTURES (SYMBOL WILL VARY)	(IP)	IP SECURITY CAMERAS
(X)	LIGHTING TRACK AND HEADS	(X)	PENDANT FIXTURES (SYMBOL WILL VARY)	(TS)	TRAFFIC COUNTER
(X)	SINGLE TUBE FLUORESCENT LIGHT FIXTURE	(X)	STAGGERED VERTICAL FLUORESCENT LIGHTS	(P)	PAGING SYSTEM CEILING SENSOR
(X)	DOUBLE TUBE FLUORESCENT LIGHT FIXTURE	(X)	RECESSED MULTI-LIGHT	(X)	SUPPLY AIR DIFFUSER
(X)	DOUBLE TUBE FLUORESCENT W/ EMERGENCY BACKUP	(X)	CEILING MOUNTED NEON SIGN	(X)	RETURN AIR DIFFUSER
(X)	DOUBLE TUBE FLUORESCENT CHAIN HUNG	(X)	SPEAKER - WHITE FINISH	(X)	TOILET EXHAUST FAN
(X)	DOUBLE TUBE FLUORESCENT CHAIN HUNG	(X)	SUBWOOFER - WHITE FINISH	(X)	LINEAR SLOT DIFFUSER
(X)	DOUBLE TUBE FLUORESCENT W/ EMERGENCY BACKUP	(X)	SPEAKER - BLACK FINISH	(X)	DUPLEX FLOOR OUTLET
(X)	DOUBLE TUBE FLUORESCENT CHAIN HUNG	(X)	FAUX SPEAKER SCREEN - WHITE FINISH	(X)	DUPLEX FLOOR OUTLET WITH DATA
(X)	DOUBLE TUBE FLUORESCENT CHAIN HUNG	(X)	FAUX SPEAKER SCREEN - BLACK FINISH	(X)	QUAD FLOOR OUTLET
(X)	RECESSED PARABOLIC FLUORESCENT FIXTURE	(X)	CURTAIN AND CURTAIN TRACK	(X)	STOREFRONT LED FIXTURES
(X)	RECESSED PARABOLIC FLUORESCENT W/ EMERGENCY BACKUP	(X)		(X)	* TAG INDICATES QTY OF FIXTURES (END-END) X NO. OF COLUMNS.
(X)	EMERGENCY LIGHT	(X)		(X)	NOTE: FOR ALL OTHER ELECTRICAL, FIRE PROTECTION, MECHANICAL, AND PLUMBING SYMBOLS REFER TO MEP DRAWINGS.

G.C. TO RE-LAMP ALL EXISTING LIGHTS. TYP. REFER TO ELECTRICAL DRAWINGS.

NOTE: ALL SECURITY DOMES, DIFFUSERS, & RETURNS ARE EXISTING TO REMAIN, U.O.N.

NOTE: ANY CEILING FIXTURE DESIGNATED AS (R) IS INTENDED TO BE RELOCATED FROM ITS PREVIOUS LOCATION. ANY CEILING FIXTURE DESIGNATED AS (N) IS A NEW FIXTURE. ANY CEILING FIXTURE NOT DESIGNATED, OR DESIGNATED AS (E) IS EXISTING TO REMAIN.

REFER TO SHEET A00.2 FOR FINISH SCHEDULE, SHEET A12.2 FOR FRAMING DETAILS, & SHEET E04.1 FOR LIGHTING SCHEDULE.

NOTE: HATCHED AREA INDICATES AREA NOT INCLUDED IN SCOPE. G.C. TO VERIFY ALL FIXTURES ARE IN GOOD WORKING CONDITION AND TOUCH UP FINISHES AS NECESSARY.