


QTY.	NO.	LOCATION	SIZE (NOMINAL)	DOOR MATERIAL	FRAME	RATING	HDWARE GROUP	DETAIL NUMBER			REMARKS / NOTES
			width x height x thickness					HEAD	JAMB	SILL	
1	①	GLASS WALL SYSTEM		1/2" TEMP. GLASS	METAL	NONE	A1	A08.3	A08.6	A08.3	PRE-FINISHED BY MFG
1	②	SALES/NON-SALES	3'-6" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	-	B1	R A12.2	R A12.2	D A12.2	-
1	③	CORRIDOR/NON-SALES	3'-6" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	-	B1	P A12.2	P A12.2	D A12.2	-
1	④	TOILET ROOM	3'-0" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	-	C1	P A12.2	P A12.2	G A12.2	-
1	⑤	REAR SERVICE	3'-6" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	45 MIN.	F	N A12.2	N A12.2	E A12.2	RATING AS REQD BY CODE
1	⑥	CLOSET	2'-0" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	-	B4	P A12.2	P A12.2	D A12.2	-
2	⑦	CLOSET	3'-6" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	-	B4	R A12.2	R A12.2	D A12.2	-
⑧	EXTERIOR ENTRY	F.R. X"X"X"X"X"X"X" 1 3/4"		GLASS	ALUMINUM	-	A3	-	-	-	-
⑨	OFFICE DOOR	3'-0" x 7'-0" x 1 3/4"		HOLLOW METAL	HOLLOW METAL	-	D	B A12.2	B A12.2	-	-
⑩	BLIND DOOR	2'-0" x 7'-0" x 1 3/4"		S.S. WOOD	WOOD	-	G1	L A12.2	L A12.2	-	-
⑪	OPERABLE DISPLAY	X" x X" (63"x75" MAX.)		GLASS	ALUMINUM	-	H	A08.5	A08.5	A08.6	BY KANNEER SERIES 120
⑫	REMOTE SERVICE	3'-6" x 7'-0" x 1 3/4"		HOLLOW METAL	HOLLOW METAL	-	K	-	-	A12.2	-
⑬	SLIDING GRILLE	X" X" X" X" X"		METAL	METAL	NONE	A8	-	-	-	W/ 3'-0" x 7'-0" EGRESS DOOR AS REQD BY CODE
⑭	SLIDING POCKET DOOR	X" X" X" X" X" 1 3/4"		WOOD	-	NONE	J	-	-	-	-
⑮	HOP CLOSET	2'-0" x 7'-0" x 1 3/4"		HOLLOW METAL	HOLLOW METAL	-	E1	L A12.2	L A12.2	-	-

DOOR NOTES

1. UNLESS NOTED OTHERWISE, GENERAL CONTRACTOR TO PAINT ALL DOORS ON SALES FLOOR PT-1 SEMI-GLOSS, AND DOORS IN NON-SALES PT-5 SEMI-GLOSS.

HARDWARE NOTES

1. DOOR HARDWARE SHALL BE OF THE LEVER OR PUSH TYPE, MOUNTED 30" TO 44" ABOVE FINISH FLOOR. FINISH SHALL BE STAINLESS STEEL AT ALL LOCATIONS. ALL DOOR HARDWARE SHALL COMPLY WITH FEDERAL AND STATE ACCESSIBILITY REQUIREMENTS.
2. ALL EXIT DOORS TO BE OPERABLE FROM INSIDE WITHOUT USE OF A KEY, SPECIAL KNOWLEDGE OR EFFORT.
3. THE FORCE REQUIRED TO OPER ANY DOOR SHALL BE MAXIMUM 5 LBS. FOR EXTERIOR DOORS AND INTERIOR DOORS.
4. ALL LOCKING HARDWARE MUST INCLUDE U-CHANGE LOCK CYLINDERS. ALL DOORS TO BE KEYED ALIKE UNLESS NOTED OTHERWISE.

GENERAL NOTES

1. DOORS AT STOREFRONT TO HAVE SIGN WITH 1" CONTRASTING LETTERING ABOVE DOORS STATING "THESE DOORS TO REMAIN UNLOCKED DURING BUSINESS HOURS".
2. EXIT DOORS TO BE OPERABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR ANY SPECIAL KNOWLEDGE OR EFFORT.
3. DOORS WITHIN THE PATH OF TRAVEL FOR ACCESSIBILITY TO BE OPERABLE WITH A SINGLE EFFORT BY LEVER, PANIC BAR OR PUSH/PULL HARDWARE.
4. DOOR HARDWARE SHALL BE OF THE LEVER OR PUSH TYPE MOUNTED 30" TO 44" ABOVE THE FLOOR AND SHALL BE OPERABLE WITH A MAXIMUM EFFORT OF 5 LBS. FOR INTERIOR DOORS AND EXTERIOR DOORS.
5. THRESHOLDS SHALL NOT EXCEED 1/2" IN HEIGHT. RAISED THRESHOLDS AND FLOOR LEVEL CHANGES AT ACCESSIBLE DOORWAYS SHALL BE BEVELED WITH A SLOPE NO GREATER THAN 1:2.
6. ALL COMPONENTS OF FIRED RATED DOOR ASSEMBLY SHALL BEAR THE LABEL OF AN APPROVED TESTING AGENCY.
7. BOTH DOORS SHALL BE FINISHED THE SAME UNLESS OTHERWISE NOTED.
8. ALL WOOD DOORS, FRAMES AND TRIM SHALL BE A.W.I. OR M.I.C. CUSTOM GRADE.
9. REFER TO MECHANICAL PLAN FOR ANY REQUIRED UNDERCUTS FOR AIR TRANSFER.

HARDWARE GROUPS

"A1" SLIDING GLAZED WALL PANELS:
DOOR IS SUPPLIED AND INSTALLED BY GLAZING CONTRACTOR.

DOOR HARDWARE AS MANUFACTURED BY NANAWALL, INC. SERIES HSN75, TOP TRACK ONLY, TOP AND BOTTOM RAILS, BRUSHED STAINLESS STEEL FINISH. CONTACT: DAVE KIRSCHBAUM (PH. 330-283-3932) (ALTERNATE CR LAURENCE, CO. INC. SERIES 5512)

HARDWARE:
DOOR SYSTEM TO RECEIVE (1) FOOT OPERATION TYPE BRUSHED STAINLESS STEEL FLOOR PIN AT EACH END. G.C. TO INSTALL U-CHANGE CYLINDER LOCKSET IN PRE-DRILLED HOLES OF SLIDING DOOR BASE, BRUSHED STAINLESS STEEL THUMB TURN ON TENANT SIDE.
VERIFY ALL HARDWARE WITH OWNER APPROVED SHOP DRAWINGS.

INSTALLATION:
REFER TO HORIZONTAL SLIDING DOOR SPECIFICATIONS ON SHEET A15.2, SECTION 081010 FOR ADDITIONAL INFORMATION/INSTALLATION INSTRUCTIONS.

INTERIOR FRAMELESS ENTRANCE DOORS: SINGLE ACTING 1/2" TEMPERED GLASS DOOR, VISTANALL GLASS SYSTEMS, (442) 551-0100, (OR OWNER APPROVED EQUAL). ALL GLAZING CHANNELS, RAILS AND DOOR

"A2" HARDWARE SHALL BE BRUSHED STAINLESS STEEL FINISH.
HARDWARE (GLAZING CONTRACTOR TO SUPPLY AND INSTALL):
• 1 EA TOP PIVOT DORMA PF-10 CENTER HUNG
• 1 EA BOTTOM PIVOT DORMA PF-10 CENTER HUNG
• 1 EA DEADBOLT: RYADON L105 WITH 1/2" D5701 THUMBTURN
• 1 EA CYLINDER U-CHANGE 30KANGWIZ WITH 626 FINISH. PHONE: (600) 541-1300, *TEAM FOXFROT!
• 2 EA PULLS OR LATCHES 21LBS 2 1/4" PULL
• 2 EA DORMA PIVOTS: RYADON L105 WITH 1/2" D5701 THUMBTURN
• 1 EA DOOR HEAD: VISTANALL FG-100 HEADER 1 VISTANALL FG-102 FILLER

EXISTING ENTRANCE DOORS:
HARDWARE:

"A4" HINGES: REPLACE WITH NON-REMOVABLE PIN HINGES
• LOCKSET: REPLACE WITH U-CHANGE PIN PHONE: (600) 541-1300, *TEAM FOXFROT!
• DOOR HOLDERS: INSTALL IVES F5462-B26D AT EACH LEAF
• MISCELLANEOUS: REPLACE HINGE STRIPPINGS AND THRESHOLD AS REQUIRED

SLIDING GRILLE:
• DAGENDORF

"A6" MODEL: "SUPRA"
• LEAD POST: COMPLETE WITH TOP AND BOTTOM LOCKING BOLTS & SECURITY FLAP
• END POST: COMPLETE WITH TOP AND BOTTOM LOCKING BOLTS
• TRACK: EXTRUDED ALUMINUM 1 3/8" X 1 1/2", CURVED TRACK SHALL BE SUPPLIED WITH 10' STANDARD RADIOS:
• EGRESS DOOR REQUIRED: SUPPLIED WITH HARDWARE 3'-0" X 7'-0" OPENING
• FINISH: CLEAR ANODIZED
• G.C. TO COORD. WITH MANUFACTURER'S RECOMMENDATIONS CONCERNING INSTALLATION AND REQUIRED SUPPORT FOR SLIDING GRILLE. G.C. TO CONTACT:
• G.C. TO FURNISHING AGENT AND MANUFACTURER 910-200-3917 BEFORE PROCEEDING WITH PLACING ANY ORDER TO GUARANTEE PROPER FIT. DOOR TO BE SUPPLIED WITH GENERAL FACTORY INSTALLED LOCK CYLINDER TO BE REPLACED WITH OWNER SUPPLIED MEDCO LOCK CYLINDER PRIOR TO TURNOVER.

SALES/NON-SALES DOOR OR NON-PUBLIC HALLWAY/NON-SALES DOOR:
HARDWARE:
"B1" • 1 1/2 PR HINGES: STANLEY F179-26D
• 1 EA PUSH PLATE: IVES 8200-B26D-4"X16"
• 1 EA PULL PLATE: IVES 8302-B-B26D-4"X16"
• 1 EA CLOSER: CORBIN RUSSWIN DC3200-M82-689 (MOUNT ON NON-SALES SIDE)
• 1 EA KICKPLATE: IVES 8400-B26D-10" X DOOR WIDTH MINUS 2"
• 1 EA DOOR HOLDER: (AT NON-RATED DOORS) IVES F5446-B26D
• 1 EA LATCHSET: (AT RATED DOORS) CORBIN RUSSWIN CL3310-NZD-626
• 1 EA SMOKE SEAL: (AT RATED DOORS) PEMKO S88W

PUBLIC HALLWAY/NON-SALES DOOR:
HARDWARE:
"B2" • 1 1/2 PR HINGES: STANLEY F179-26D
• 1 EA LATCHSET: U-CHANGE #45L52D502 WITH RHODES-STYLE LEVER AND 626 FINISH. (SPECIFY DOOR HANDING WHEN ORDERING) PHONE: (600) 541-1300, *TEAM FOXFROT!
• 1 EA CLOSER: CORBIN RUSSWIN DC3200-M82-689 (MOUNT ON NON-SALES SIDE)
• 1 EA KICKPLATE: IVES 8400-B26D-10" X DOOR WIDTH MINUS 2"
• 1 EA DOOR HOLDER: (AT NON-RATED DOORS) IVES F5446-B26D
• 1 EA SMOKE SEAL: (AT RATED DOORS) PEMKO S88W

REMOTE STOCKROOM DOOR:
HARDWARE:
"B3" • 1 1/2 PR HINGES: STANLEY F179-26D WITH NON-REMOVABLE PIN
• 1 EA LATCHSET: U-CHANGE #45L52D502 WITH RHODES-STYLE LEVER AND 626 FINISH. (SPECIFY DOOR HANDING WHEN ORDERING) PHONE: (600) 541-1300, *TEAM FOXFROT!
• 1 EA CLOSER: CORBIN RUSSWIN DC3200-M82-689 (MOUNT ON NON-SALES SIDE)
• 1 EA KICKPLATE: IVES 8400-B26D-10" X DOOR WIDTH MINUS 2"
• 1 EA DOOR HOLDER: (AT NON-RATED DOORS) IVES F5446-B26D
• 1 EA SMOKE SEAL: (AT RATED DOORS) PEMKO S88W

NON-PUBLIC HALLWAY/CLOSET DOOR:
HARDWARE:
"B4" • 1 1/2 PR HINGES: STANLEY F179-26D
• 1 EA LATCHSET: CORBIN RUSSWIN CL3320-NZD-626
• 1 EA DOOR STOP: IVES #5402-B26D
• 1 FLUSHBOLT: IVES 43, 26D 12" (AT TOP OF INACTIVE LEAF OF DOUBLE DOOR)

TOILET ROOM DOOR: UNFINISHED HOLLOW METAL DOOR & FRAME
HARDWARE:
"C1" • 1 1/2 PR HINGES: STANLEY F179-26D
• 1 EA LATCHSET: CORBIN RUSSWIN CL3320-NZD-626
• 1 EA KICKPLATE: IVES 8400-B26D-10"X34"
• 1 EA DOOR STOP: IVES #5402-B26D
• 1 EA HOOK: ROCKWOOD 806-B26D CENTERED ON DOOR AT 72" AFF
• 1 EA CLOSER: (AT RATED DOORS) CORBIN RUSSWIN DC3200-M82-689 (MOUNT ON TOILET ROOM SIDE)
• 1 EA SMOKE SEAL: (AT RATED DOORS) PEMKO S88W

"E0" ELEVATED TOILET ROOM DOOR:
HARDWARE:
• 2 PR HINGES: STANLEY 6D91-326 4-1/4" X 4-1/2" (OWNER PROVIDED)
• 1 EA LATCHSET: NANK-209 LEVER HANDLE 5 1/2" L, W/ 5686 ROSETTE. FURNISHED BY OWNER.
• 1 EA DOOR STOP: IVES #5402-B26D
• 1 EA CLOSER: CORBIN RUSSWIN DC6200-SERIES 625 BRIGHT CHROMIUM
• 1 EA SMOKE SEAL (AT RATED DOOR) PEMKO S88W

"E1" OFFICE DOOR:
HARDWARE:
• 1 1/2 PR HINGES: STANLEY F179-26D WITH NON-REMOVABLE PIN
• 1 EA LATCHSET: NANK-209 LEVER HANDLE 5 1/2" L, W/ 5686 ROSETTE. FURNISHED BY OWNER.
WHEN ORDERING: PHONE: (600) 541-1300, *TEAM FOXFROT!
• 1 EA KICKPLATE: IVES 8400-B26D-10"X4"
• 1 EA DOOR STOP: IVES #5402-B26D
• 1 EA HOOK: ROCKWOOD 806-B26D CENTERED ON DOOR AT 72" AFF
• 1 EA CLOSER: (AT RATED DOORS) CORBIN RUSSWIN DC3200-M82-689 (MOUNT ON OFFICE SIDE)
• 1 EA SMOKE SEAL (AT RATED DOORS) PEMKO S88W

"E2" HOP SINK/CLOSET DOOR:
HARDWARE:
• 1 1/2 PR HINGES: STANLEY F179-26D
• 1 EA LATCHSET: NANK 202 LEVER HANDLE 5 1/2" L, W/ 5686 ROSETTE. FURNISHED BY OWNER.
• 1 EA DOOR STOP: IVES #5402-B26D
• 1 EA HOOK: ROCKWOOD 806-B26D CENTERED ON INSIDE OF DOOR AT 72" AFF
• 1 EA DEADBOLT: CORBIN RUSSWIN SARGENT 467, BRONZE SATIN FINISH (MOUNT AT 36" AFF)
• 1 EA CYLINDER: U-CHANGE 30KANGWIZ WITH 626 FINISH. PHONE: (600) 541-1300, *TEAM FOXFROT!

"E3" ELEVATED HOP SINK DOOR: HOLLOW METAL DOOR WITH 1/4" VENEER AND HARD WOOD TRIMS APPLIED
HARDWARE:
• 1 1/2 PR HINGES: STANLEY F179-26D
• 1 EA LATCHSET: NANK 202 LEVER HANDLE 5 1/2" L, W/ 5686 ROSETTE. FURNISHED BY OWNER.
• 1 EA DOOR STOP: IVES #5402-B26D
• 1 EA HOOK: ROCKWOOD 806-B26D CENTERED ON INSIDE OF DOOR AT 72" AFF
• 1 EA DEADBOLT: CORBIN RUSSWIN SARGENT 467, BRONZE SATIN FINISH (MOUNT AT 36" AFF)
• 1 EA CYLINDER: U-CHANGE 30KANGWIZ WITH 626 FINISH. PHONE: (600) 541-1300, *TEAM FOXFROT!

"F" SERVICE DOOR:
HARDWARE:
• 3 PR HINGES W/SECURITY STUDS BY G.C.: IVES 55B15H
• 1 EA PANIC HARDWARE: TRIDENT TEL-210 (SUPPLIED BY OWNER, INSTALLED BY G.C.) WITH U-CHANGE CYLINDER. MOUNT AT 45" AFF OR AS REQUIRED BY CODE
• 1 EA CLOSER: CORBIN RUSSWIN DC3210-M82-689
• 1 EA KICKPLATE: IVES 8400-B26D-10" X DOOR WIDTH MINUS 2"
• 1 EA VENEER: IVES W49-B26D CENTERED ON DOOR AT 54"
• 1 EA LOCK PROTECTOR: GLYNN JOHNSON #LPI-US32D
• 1 EA DOOR SWEEP: (AT EXTERIOR LOCATION) PEMKO 216AV
• 1 EA DOOR SEAL: (AT EXTERIOR OR RATED DOORS) PEMKO S88W
• 1 EA THRESHOLD: (AT EXTERIOR LOCATION) PEMKO 270A
• 1 EA DOOR CONTACT: (AT EXTERIOR LOCATION) INSTALLED BY OWNER
• 1 EA SIGN PLAQUE: BY OWNER

AT EXISTING SERVICE DOORS, PROVIDE AND INSTALL HARDWARE AS NEEDED TO MEET THE ABOVE REQUIREMENTS. ALSO REMOVE OUTSIDE LEVER/LOCK AND INSTALL BLANK COVER PLATES TO CONCEAL HOLES AND PAINT ENTIRE DOOR PER MALL'S REQUIREMENTS.

ALL DOORS TO RECEIVE PANIC HARDWARE AS SPECIFIED ABOVE.

"G1" BLIND DOORS (SALES):
HARDWARE:
• 1 1/2 PAIR HINGES PER LEAF - STANLEY F179-26D
• 1 EA DEADBOLT: CORBIN RUSSWIN DL211, 626 (MOUNT AT 36" AFF)
• 1 EA FULL CATCH PIN - 0345-264 - SATIN CHROME (MOUNT AT 42" AFF)
• 1 EA ROLLER CATCH: IVES 336-26D
• 1 FLUSHBOLT: IVES 43, 26D 12" (AT TOP OF INACTIVE LEAF OF DOUBLE DOOR)

"G2" BLIND DOORS (NON-SALES):
HARDWARE:
• 1 EA HINGE: FULL HEIGHT HEAVY DUTY PIANO HINGE, 26D
• 1 EA DEADBOLT: CORBIN RUSSWIN DL211, 626 (MOUNT AT 36" AFF)
• 1 EA WIRE PULL: IVES 336-26D 4" (MOUNT AT 42" AFF)
• 1 EA ROLLER CATCH: IVES 336-26D
• 1 EA DOOR STOP: IVES #5402-B26D

"H" OPERABLE DISPLAY WINDOW: ALUMINUM-FRAMED DOOR WITH 1/4" TEMPERED GLASS: KANNEER 120 NARROW STYLE WITH BEVELED STOP. 2 1/4" STYLE, 2 1/4" TOP AND BOTTOM RAILS. FINISH TO MATCH KANNEER INTERPON D2000 BONE WHITE

"H1" HINGE: ROTON FULL HEIGHT ALUMINUM HINGE, CLEAR ANODIZED FINISH
• 1 EA LOCKSET: STANDARD KANNEER LOCKSET W/ 26D FINISH. MOUNT 44" AFF. ALL DOORS TO BE KEYED ALIKE.
"J1" SLIDING GRILLE POCKET DOOR (SALES):
HARDWARE:
• 1 EA HINGE: FULL HEIGHT HEAVY DUTY PIANO HINGE, 26D
• 1 EA PULL: IVES 806-26D 4" (MOUNT AT 42" AFF)
• 2 EA MAGNETIC CATCH (1 CATCH AT 2' 0" AFF, 1 CATCH AT 8' 0" AFF)
• 1 METAL KICK PLATED INSTALLED AT BASE OF DOOR, FINISHED 11T-2
• 1 EA DEADBOLT: CORBIN RUSSWIN DL211, 626 (MOUNT AT 36" AFF)

"K" REMOTE STORAGE DOOR (SERVICE DOOR):
HARDWARE:
• 3 PR HINGES W/SECURITY STUDS BY G.C.: IVES 55B15H
• 1 EA LOCKSET:
• 1 EA CLOSER: INSTALL SIMPLY KEYPAD LEVER LOCK SERIES L4900 MODEL 1051A-26D PROVIDED AND INSTALLED BY G.C. ORDER THRU 1-800-541-1300, *TEAM FOXFROT!
CANADA STORES: INSTALL U-CHANGE CYLINDER LOCK 1/4" THUMB TURN ON INSIDE. ORDER THRU 1-800-541-1300, *TEAM FOXFROT!
• 1 EA CLOSER: CORBIN RUSSWIN DC3210-M82-689
• 1 EA KICKPLATE: IVES 8400-B26D-10" X DOOR WIDTH MINUS 2"
• 1 EA WIENER: IVES W49-B26D CENTERED ON DOOR AT 54"
• 1 EA LOCK PROTECTOR: GLYNN JOHNSON #LPI-US32D
• 1 EA DOOR SWEEP: (AT EXTERIOR LOCATION) PEMKO 216AV
• 1 EA DOOR SEAL: (AT EXTERIOR OR RATED DOORS) PEMKO S88W
• 1 EA THRESHOLD: (AT EXTERIOR LOCATION) PEMKO 270A
• 1 EA DOOR CONTACT: (AT EXTERIOR LOCATION) INSTALLED BY OWNER
• 1 EA SIGN PLAQUE: BY OWNER

AT EXISTING SERVICE DOORS, PROVIDE AND INSTALL HARDWARE AS NEEDED TO MEET THE ABOVE REQUIREMENTS. ALSO REMOVE OUTSIDE LEVER/LOCK AND INSTALL BLANK COVER PLATES TO CONCEAL HOLES AND PAINT ENTIRE DOOR PER MALL'S REQUIREMENTS.

ALL DOORS TO RECEIVE PANIC HARDWARE AS SPECIFIED ABOVE

CODE	MATERIAL	MANUFACTURER	DESCRIPTION	LOCATION / NOTES
PAINT FINISHES				
PT-1	PAINT	BENJAMIN MOORE	NO. 844 - "ALOE VERA"	SATIN IMPERVO # 314 AT WALLS, FLAT AT CEILING & REGAL AQUA GLO SEMI-GLOSS AT TRIM/BASE UNLESS NOTED OTHERWISE
PT-5	PAINT	BENJAMIN MOORE	NO. 876 - "WHITE"	NON-SALES, CORRIDORS, # DOORS: SATIN FINISH AT WALLS, FLAT AT CEILINGS
PT-11	VARNISH	GREEN DOLPHIN	FIRE SAFE 108 WOOD INTUMESCENT FIRE RETARDANT WOOD TREATMENT	FOR USE WITH SF-2 & NON-SALES SHELVING (WHEN REQD)
PT-12	PAINT	BENJAMIN MOORE	NO. 0062 - "BABY'S BREATH"	EXTERIOR GRADE BOARD & INTERIOR OF ILLUMINATED TRANSOM; HIGH GLOSS
PT-13	PAINT	BENJAMIN MOORE	NO. 0C-5 - "MARITIME WHITE"	FLAT AT TOILET ROOM CEILING SATIN AT TOILET ROOM DOOR JAMB REVEALS
PT-15	PAINT	BENJAMIN MOORE	NO. 2130-20 - "DEEP CAVIAR"	BACK WALL OF BACKWRAP VIDEO MONITOR DISPLAY (DOMESTIC)
PT-16	PAINT	BENJAMIN MOORE	TO MATCH PANTONE #294 (SEMIGLOSS)	WALL ABOVE BREAK AREA BAR COUNTER
PT-17	PAINT	SHERWIN WILLIAMS	NO. 2065-20 "DARK ROYAL BLUE" (SATIN)	STANDARD BARRICADE
FLOOR COVERINGS				
FC-4	VINYL COMPOSITE TILE	ARMSTRONG	EXCELON NO. 51901 - "TAUPE", IMPERIAL TEXTURE	NON-SALES FLOOR
FC-5	VINYL COMPOSITE TILE	ARMSTRONG	EXCELON NO. 51816 - "CHERRY RED", IMPERIAL TEXTURE	NON-SALES FIRE LANE, IN FRONT OF ELECTRICAL PANELS
FC-12	PORCELAIN	INNOVATIVE MARBLE AND TILE INC.	180630, ROVERS 7-5/8" X 36" X 3/16" WITH 1/4" GROUT JOINTS	SALES AREA FLOOR
FC-13	VINYL COMPOSITE TILE	ARMSTRONG	EXCELON NO. 51869 - "MUMMUS" IMPERIAL TEXTURE	NON-SALES PROCESSING AREA ONLY
FC-14	WALK-OFF MAT	MAXIMUS	DESIGNER LINK "CAFARI" CARPET IV- TAFEAST-BACKING IN DARK BROWN, PVS-GRATE 30" X 60" X 1/2"	INTERIOR WALK-OFF MAT FOR EXTERIOR STORES
FC-18	PORCELAIN TILE	CROSSVILLE	"CHESTNUT" - 6" X 24" X 3/8" & 6" X 36" X 3/8" TILE W/ 1/8" GROUT JOINT	PACKAGE I SALES AREA; RANDOM PATTERN FROM SIDE TO SIDE OF STORE
FC-19	TILE	SICILIAN WHITE TILE STUDIOS	SICILIAN WHITE TILE 13"x13"	TOILET ROOM
FC-20	CERAMIC TILE	CAESAR CERAMICS	24" X 24" ABSOLUTE PORCELAIN TILE "WHITE STAR" - LAPFIRE HONEY FINISH FIELD CUT WITH CONCEALED EDGES	EXTERIOR STOREFRONT BASE
B-1	VINYL BASE	ARMSTRONG	NO. 03 - "BISQUEWARE", 4" HIGH (6" AT TOILET ROOM)	NON-SALES # CORRIDOR
B-2	WOOD BASE	L.T. CUSTOM FIXTURES	4" HIGH OAK WOOD BASE - FIELD VERIFY	PASS THRU AND FOCAL LOCATIONS AS SPECIFIED
B-3	WOOD BASE		PAINT GRADE POPLAR	PAINT PT-1, U.O.N.
B-5	WOOD BASE	L.T. CUSTOM FIXTURES	4" HIGH OAK WOOD BASE (TRANSVERSE GRAIN)	UNIT 5B, PASS THRU PORTAL, & CONCIERGE CASHWRAP PORTAL
B-6	WOOD BASE	L.T. CUSTOM FIXTURES	1/4" THICK 4" HIGH (SCRIBABLE) WOOD BASE (TRANSVERSE GRAIN) WITH QUIRK	UNIT 5B/5C, PASS THRU PORTAL, & CONCIERGE CASHWRAP PORTAL
WALL COVERINGS				
T-1	CERAMIC TILE	DALTILE 800-365-8453	SEMI-GLOSS - "WHITE 0100" - 3" x 6" (FIELD TILE), 1/8" JOINTS	STANDARD TOILET ROOMS & BACKWALL AT DRINKING FOUNTAIN (BY G.C.)
T-3	CERAMIC TILE	DALTILE 800-365-8453	LINERS - "WHITE 0100" - 2" x 6" (CHAIR RAIL), 1/8" JOINTS	STANDARD TOILET ROOMS & BACKWALL AT DRINKING FOUNTAIN (BY G.C.)
T-5	CERAMIC TILE	DALTILE 800-365-8453	"DM 14 COBALT" - 1" x 6" (LINER BAR), 1/8" JOINTS	STANDARD TOILET ROOMS & BACK WALL AT DRINKING FOUNTAIN (BY G.C.)
T-6	TILE	WALKER ZANGER	VINTAGE GLASS "PEARL LUSTER" 1"x1" MOSAIC TILE	PASS THRU NICHE, DEMO SINK, 9 NICHE (BY OWNER)
T-7	TILE	ATLAS CONCORDE	STUDIO LINE A, 11 5/8" X 23 3/8", POLISHED, 88 WHITE, 1/8" JOINTS	ELEVATED RESTROOM WALLS (BY OWNER)
MT-2	METAL PANELS	LAMBERT	MATCH KANNEER "INTERPON D2000 BONE WHITE"	STOREFRONT METAL PANELS
MT-3	METAL PANELS	LAMBERT	TO MATCH BENJAMIN MOORE HC-41 - "RICHMOND GOLD"	BASE & REVEAL AT STOREFRONT (PLANKING SIDE)
WD-3	WOOD	L.T. CUSTOM FIXTURES	FLAT CUT WHITE OAK WITH CLEAR FINISH	TRIMS / CABINETS/ STOREFRONT & PASS-THRU PORTAL
WD-4	WHITE TRIM	L.T. CUSTOM FIXTURES	PREFINISHED WHITE TRIM - VARIOUS PROFILES	TRIMS / CABINETS/ BACKWRAP SURROUNDS
WC-1	WALL COVERING	DREAMSCAPE	BLUE GINGHAM WALL COVERING	WALLS TO BE PRIMED, PAINTED PT-1 AND SIZING PRIMED PRIOR TO WALL COVERING INSTALLATION.
WE-3	WALL COVERING	RUSSELES	CUSTOM WALLGRAPHIC	ADVERTISE BREAK AREA
CEILING				
ACT-1	ACOUSTICAL CEILING TILE	ARMSTRONG	PUNE NO. 174 - 24" x 24" TILE ON 21X21 STAGNANT GRID 15/16" X1 EXPOSED TILE SURFACES/EDGES	SALES AREA CEILING: TILE AND GRID TO BE WHITE.
ACT-2	ACOUSTICAL CEILING TILE	ARMSTRONG	CORTEGA NO. 741 - 24" x 24" NON-DIRECTIONAL FIGURED ON PRELUDE XL 15/16" EXPOSED TEE GRID	NON-RATED CORRIDOR CEILING. TILE AND GRID TO BE WHITE.
ACT-3	1 1/8" RATED CEILING TILE	ARMSTRONG	PIRUS NO. 377 - 24" x 24" x 3/4" FIRE RESISTANT TILE ON SUPRATINE 5/8" FIRE RESISTANT GRID	SALES AREA CEILING: TILE AND GRID TO BE WHITE.
ACT-4	1 1/8" RATED CEILING TILE	ARMSTRONG	CORTEGA NO. 025 - 24" x 24" x 3/4" FIRE RESISTANT TILE ON PIRASGLO 15/16" GRID	RATED CORRIDOR CEILING TILE AND GRID TO BE WHITE.
GROUTS / SEALANTS				
S-2	ADHESIVE	G.E.	1200 SERIES SILICONE	FOR USE WITH MT-2 & MT-3 FOR STOREFRONT METAL INSTALLATION
S-4	WOOD SEALER	BID	WATER-BASE POLYURETHANE, CLEAR SATIN FINISH	NON-SALES WOOD SHELVES
S-5	GROUT	LATICRETE	NO. 44 - "BRIGHT WHITE"	FOR USE WITH T-1, T-3, T-5 & FC-20 (BY G.C.)
S-11	GROUT	HYDROMENT	NO. H41 - "FLASH WALNUT"	FOR USE WITH FC-18 UNBANDS (BY G.C.)
S-12	GROUT	STARGLASS	NO. 600 - "DIAMOND"	FOR USE WITH T-6 (BY OWNER)
S-13	GROUT	HYDROMENT	NO. H15B - "CLASSIC BONE"	FOR USE WITH FC-19 & T-7 (BY G.C.)
GLASS				
G-2	DISPLAY GLASS	BID	1/4" CLEAR TEMPERED GLASS	OPERABLE DISPLAY WINDOW
G-3	INSULATED STOREFRONT GLASS	BID	1" CLEAR INSULATED TEMPERED GLASS	EXTERIOR STOREFRONT CONDITIONS OF 5 - UNLESS OTHERWISE NOTED
G-4	STOREFRONT GLASS	BID	1/2" CLEAR TEMPERED GLASS	AT STOREFRONT DISPLAY WINDOWS, FRAMELESS DOORS & SIDELITES (INTERIOR MALL LOCATION)
G-5	STOREFRONT GLASS	BID	3/4" CLEAR TEMPERED GLASS	AT STOREFRONT DISPLAY WINDOWS, FRAMELESS DOORS & SIDELITES (INTERIOR MALL LOCATION)
G-6	LAMINATED STOREFRONT GLASS	BID	3/8" CLEAR LAMINATED TEMPERED GLASS	EXTERIOR STOREFRONT CONDITIONS REQUIRING HURRICANE RESISTANCE
G-7	STOREFRONT GLASS	BID	1/2" STARPHIRE GLASS	AT STOREFRONT ILLUMINATED TRANSOM ABOVE ENTRANCE (INTERIOR MALL LOCATIONS WHEN G-8 IS NOT PERMITTED BY ENGINEER)
G-8	STOREFRONT PLEX	BID	1/2" CLEAR PLEX	AT STOREFRONT ILLUMINATED TRANSOM ABOVE ENTRANCE (INTERIOR MALL LOCATIONS WHEN G-8 IS NOT PERMITTED BY ENGINEER)
G-9	INSULATED STOREFRONT GLASS	BID	1" STARPHIRE INSULATED GLASS	AT STOREFRONT ILLUMINATED TRANSOM ABOVE ENTRANCE (EXTERIOR MALL LOCATIONS)
G-11	STOREFRONT GLASS	ALL NEW GLASS	1" INSULATED NON-GLARE GLASS	EXTERIOR STOREFRONT CONDITIONS OF 5 - TO COORDINATE WITH OWNER'S PURCHASING AGENT IN WEEK 12 OF CONSTRUCTION
G-12	POLYCARBONATE	DIGICO	1/2" POLYCARBONATE PANEL WITH GINGHAM AND DIFFUSING FILMS	BACKLIT GINGHAM STOREFRONT WALLS
SPECIAL FINISHES				
SF-1	FIBERGLASS REINFORCED POLYESTER	BID	1/4" F.R.P. PANELING WITH CORNER & J MOLDINGS AS REQUIRED, COLOR: WHITE	ALL EXPOSED NON-SALES WALLS. SEE A05.1 ADJACENT WALLS TO MOP SINK
SF-2	SHIPLAP PLANKING	L.T. CUSTOM FIXTURES	3/4" THICK: 9" WIDE W/ 3/4" EXPOSED LAP AT STOREFRONT & 3/4" TO 7/8" AT BACKWRAP	CLASS 1A STOREFRONT PLANKING; ORIENT HORIZONTALLY; ACHIEVE FULL PLANK TOP AND BOTTOM AT BACKWRAP
SF-3	SOLID SURFACE	CAESAR CERAMICS	60 SQ CM (APPROX. 23 5/8" X 23 5/8") ABSOLUTE PORCELAIN TILE "WHITE STAR" - MATTE FINISH, CUT IN FIELD, CONCEAL CUT EDGES	STOREFRONT PIERS - ALTERNATE WITH SF-4
SF-4	SOLID SURFACE	CAESAR CERAMICS	60 SQ. CM (APPROX. 23 5/8" X 23 5/8") ABSOLUTE PORCELAIN TILE "WHITE STAR" - LAPFIRE FINISH, CUT IN FIELD, CONCEAL CUT EDGES	STOREFRONT PIERS - ALTERNATE WITH SF-3
SF-5	GLAZING FILM	COOLVU	1/4" FILM - WP6 COOLVUHD - CLEAR	EXTERIOR STOREFRONT CONDITIONS
SF-6	MALL MATCH FLOORING	TO MATCH MALL SPEC.	TO MATCH MALL STANDARD	FROM LEASE LINE TO CLOSURE LINE
SF-8	GLAZING FILM	3M	CONTROL TAC PLUS GRAPHIC FILM SERIES 166 - COLOR: DARK GREY #866-41	SPANDREL GLASS
SF-9	GLAZING FILM	3M	CONTROL TAC PLUS GRAPHIC FILM SERIES 166 - COLOR: SCOTCHGAL WHITE #666-25	SPANDREL GLASS; FOR LOCATIONS WHERE STRUCTURAL FRAMING IS RIGHT BEHIND GLASS
SF-10	EXTERIOR SHIPLAP PLANKING	L.T. CUSTOM FIXTURES	EXTERIOR GRADE WHITE OAK PREFINISHED BY VENDOR 3/4" THICK 9" WIDE W/ 3/4" EXPOSED LAP PLANKING	STOREFRONT PLANKING; ORIENT HORIZONTALLY (EXTERIOR LOCATIONS)
SF-12	GLAZING FILM	3M	DIFFUSER FILM WHITE 3035-36 (308 LIGHT TRANSMISSION)	APPLY FILM TO INTERIOR SIDE OF TRANSOM GLASS PRIOR TO GLASS INSTALLATION
SF-14	GLASS	DEMHEIM	"BEM BLUE" LAMINATED SAFETY GLASS	DEMONSTRATION SINK
PL-1	PLASTIC LAMINATE	FORMICA	NO. 933-58 "MISSION WHITE" MATTE	CASHWRAP/BACKWRAP COUNTERTOP