

PLUMBING & FIRE PROTECTION RESPONSIBILITY SCHEDULE							
ITEM	FURNISHED BY		INSTALLED BY		RE-USE EXISTING	N/A	REMARKS
	LSKORC VENDOR	LANDLORD	CONTR.	LANDLORD			
PLUMBING FIXTURES & TRIM			GC		GC		
DRINKING FOUNTAIN AND ASSOCIATED ACCESSORIES.	LD				GC		
SEWER AND VENT PIPING			GC		GC		
TANK WATER HEATER			GC		GC		
DOMESTIC HOT AND COLD WATER PIPING			GC		GC		
CONDENSATE DRAIN PIPING			GC		GC		
SECOND CONDENSATE DRAIN PIPING							●
CONDENSATE DRAIN PUMP							●
GAS PIPING			GC		GC		
FLOOR DRAINS, CLEANOUTS, WATER HAMMER ARRESTORS, ETC.			GC		GC		
INSTANTANEOUS WATER HEATER	LD				GC		
DEMO SINK LAV AND FAUCET	LD				GC		FOR COB/BBW STORES ONLY
DRAIN PUMP							● FOR COB/BBW STORES ONLY
SPRINKLER PIPING			FPC		FPC		
SPRINKLER HEADS			FPC		FPC		
FIRE EXTINGUISHERS			FPC		FPC		
AS-BUILTS DRAWINGS			GC				

ABBREVIATIONS, RESPONSIBILITY SCHEDULES			
FPC	FIRE PROTECTION CONTRACTOR	LD	LIGHTING PACKAGE DISTRIBUTOR
AHJ	AUTHORITY HAVING JURISDICTION	LL	LANDLORD
GC	GENERAL CONTRACTOR	LS&DC	LIMITED STORE DESIGN & CONSTRUCTION
LC	LANDLORD CONTRACTOR	MC	MECHANICAL CONTRACTOR

RESPONSIBILITY SCHEDULE-BBW	NTS	L 09/13/13
	42N-P0101-G00-SCHD	

ABBREVIATIONS - PLUMBING					
AD	ACCESS DOW	G	GAS	PM	PROJECT MANAGER
ADA	AMERICAN DISABILITY ACT	GC	GALLONS	POC	POINT OF CONNECTION
ADF	ABOVE FINISHED FLOOR	GL	GENERAL CONTRACTOR	PRV	PRESSURE REDUCING VALVE
AP	ACCESS PANEL	GPB	GALLONS PER MINUTE	PSI	POUNDS PER SQUARE INCH
CD	CEILING DIFFUSER OR CONDENSATE DRAIN	HB	HOSE BIBB	(R)	RELOCATE
CFM	CUBIC FEET PER MINUTE	HD	HEAD	RD	ROOF DRAIN
CM	CAST IRON	HP	HORSEPOWER	RPBP	REDUCES PRESSURE
CO	CLEANOUT	HW	HOT WATER	RF	REDUCES FLOW
CONT	CONTINUE			RFM	REVOLUTION PER MINUTE
CONTR	CONTRACTOR	INV	INVERT		
COTG	CLEANOUT TO GRADE	LAV	LAVATORY	SCH	SCHEDULE
OW	COLD WATER	LB	POUND	SOV	SHUT-OFF VALVE OR SCHEDULE OF VALVE
		LF	LINEAL FEET		
DET	DETAIL			UH	UNIT HEATER
DF	DRAINING FOUNTAIN	UN	UNLESS OTHERWISE NOTED	UTR	UP THRU ROOF
DL	DOOR LOUVER	MECH	MECHANICAL MANUFACTURER		
DS	DREAMSTEAMER	MTO	MOUNTED		
DTR	DOWN THRU ROOF	WTR	MOTOR	VTR	VENT THRU ROOF
DWG	DRAWING				
(E)	EXISTING	(N)	NEW	WC	WATER CLOSET
EW	ELECTRIC WATER COOLER	N.C.	NORMALLY CLOSED	WCO	WALL CLOUET
FCU	FLOOR CLEANOUT	N.I.C.	NOT IN CONTRACT	WH	WATER HAUSER
FCO	FAN COIL UNIT	N.O.	NORMALLY OPEN	WHH	WATER HAMMER ARRESTER
FDC	FLOOR DRAIN	N/A	NOT APPLICABLE	WT	WEIGHT
FID	FURNISHED BY OWNER.	NTS	NOT TO SCALE		
	INSTALLED BY CONTRACTOR	P	PUMP		
FFC	FIRE PROTECTION CONTRACTOR	PC	PLUMBING CONTRACTOR		
FFS	FEET PER SECOND	PD	PRESSURE DROP		
FS	FLOOR SINK	PLBG	PLUMBING		

PLUMBING ABBREVIATIONS	NTS	J 09/06/13
	00N-P0101-J00-ABBR	

INTERIOR DOMESTIC WATER: TYPE 'K' RIGID COPPER WITH SOLDER TYPE WROUGHT COPPER FITTINGS, MADE UP WITH NO LEAD SOLDER. PIPING UNDER SLAB TO BE TYPE 'K' SOFT DRAWN COPPER WITH NO JOINTS PERMITTED BELOW SLAB. SLEEVE ALL PENETRATIONS THRU SLAB.

EXTERIOR DOMESTIC WATER: TYPE 'K' SOFT DRAWN COPPER WITH FLARE FITTINGS ONLY.























INTERIOR SANITARY SOIL, WASTE, AND VENT: STANDARD WEIGHT CAST IRON PIPE WITH STANDARD WEIGHT FITTINGS, LEAD JOINTS, OR NO-HUB CAST IRON SYSTEM AND JOINTS. IN ACCORDANCE WITH LOCAL CODE. VENTS SHALL BE CAST IRON AS ABOVE OR SCHEDULE 40 GALVANIZED STEEL WITH GALVANIZED MALLEABLE SCREWED FITTINGS. PVC OR ABS IS OPTIONAL PER LOCAL CODE.

EXTERIOR SANITARY SEWER: SCHEDULE 40 PVC PIPE AND FITTINGS WITH SOLVENT CEMENTED JOINTS OR EXTRA STRENGTH C-200 VITREOUS CLAY PIPE AND FITTINGS WITH ELASTOMERIC JOINTS.




























DOMESTIC WATER PIPE INSULATION: FLEXIBLE ELASTOMERIC THERMAL INSULATION, EXPANDED CLOSED CELL OR MOLDED, SECTIONAL FIBROUS GLASS WITH FACTORY APPLIED, UL LISTED VAPOR BARRIER JACKET BOTH WITH A FLAME SPREAD OR 25 OR LESS AND A THERMAL RESISTANCE VALUE OF 3.6 - 4.5 (HR) (SQ FT) (F DEG PER IN.) PER BTU. REFER TO DETAIL FOR EXTENT OF INSTALLATION.

GAS PIPE: SCHEDULE 40 BLACK STEEL WITH SCREWED CONNECTIONS, GAS LINE BELOW GRADE TO BE "COATED AND WRAPPED" AND HAVE CATHODIC PROTECTION WITH ANODES WELDED TO PIPE. SIZE AND NUMBER OF ANODES AS RECOMMENDED BY LOCAL GAS COMPANY. ALL THREADS, TOOL MARKS, SCRATCHES, AND WELDED ANODE PORTIONS TO BE ALSO "COATED AND WRAPPED" PRIOR TO BACKFILLING. ALL GAS LINES ROUTED IN CEILING SPACE AND CONCEALED IN WALL TO HAVE WELDED JOINTS AND FITTINGS.

	NTS
PIPING MATERIAL SPECIFICATION	

ITEM	FIXTURE	ROUGH-IN SERVICES						DESCRIPTION	REMARKS
		CW	HW	W	V	M	GAS		
	WATER CLOSET TANK TYPE	½"	-	4"	2"	-	-	KOHLER "HIGHLINE PRESSURE LITE" MODEL NO. K-3519, 1.1 GPF, PRESSURE ASSISTED WHITE WATER CLOSET WITH ELONGATED VITREOUS CHINA BOWL, (OR ZURN MODEL 2556), 1.0 GPF WITH HIGH PERFORMANCE ECOTUSH TECHNOLOGY), 1½" HIGH, WHITE OPEN FRONT SEAT AND COOL #4550. FURNISH WITH BOLT CAPS AND CHROME SUPPLY STOP. (FOR PUBLIC NON-PUBLIC RESTROOMS), FLUSH LEVER SHALL BE LOCATED ON THE WIDE SIDE OF THE TOILET.	ACCESSIBLE TYPE
	"STANDARD RESTROOM" LAVATORY, WALL-MOUNTED	½"	¾"	2"	1½"	-	-	KOHLER "CHESAPEAKE 20" X 16" LAVATORY, MODEL NO. K-1729 (OR AMERICAN STANDARD "COMRADE" WALL-MOUNT SINK, MODEL NO. 0124131), FURNISH WITH CONCEALED AMN WALL HANGER, CHROME SUPPLY STOPS, P-TRAP, KOHLER LEVER-OPERATED "CORALIAS" FAUCET MODEL NO. K-5182-F WITH POP-UP DRAIN AND 0.5 GPM AERATOR, INSULATE P-TRAP AND SUPPLY LINES WITH ½" ARMOSTRONG "ARMATEX" PIPING INSULATION OR EQUIVALENT, MOUNT AT HEIGHT DIRECTED BY THE ARCHITECT. (FOR NON-PUBLIC RESTROOMS)	ACCESSIBLE TYPE
	"BW ELEVATED RESTROOM" LAVATORY/ DEMO SINK	½"	¾"	2"	1½"	-	-	DURAVIT COUNTER-MOUNTED LAVATORY, MODEL NO. #031578. FURNISH WITH CHROME SUPPLY STOPS AND P-TRAP, DORNBRACH #HEM 3231578S FAUCET WITH POP-UP DRAIN AND 0.5 GPM AERATOR, INSULATE P-TRAP AND SUPPLY LINES WITH ½" ARMOSTRONG "ARMATEX" PIPING INSULATION OR EQUIVALENT.	ACCESSIBLE TYPE
	"BW ELEVATED RESTROOM" LAVATORY, WALL-MOUNTED	½"	¾"	2"	1½"	-	-	DURAVIT WALL-MOUNTED LAVATORY, MODEL NO. #045840 WHITE, FINISH-WITH CONCEALED AMN WALL HANGER, CHROME SUPPLY STOPS, P-TRAP, CHROME PLATED GRD DRAIN, DORNBRACH #HEM 3352178S FAUCET (W/O POP-UP DRAIN) AND 0.5 GPM AERATOR, INSULATE P-TRAP AND SUPPLY LINES WITH ½" ARMOSTRONG "ARMATEX" PIPING INSULATION OR EQUIVALENT, MOUNT AT HEIGHT DIRECTED BY THE ARCHITECT. (FOR NON-PUBLIC RESTROOMS)	ACCESSIBLE TYPE
	WATER HEATER INSTANTANEOUS	¾"	½"	-	-	-	-	CHRONOMET INSTANT-FLOW #M-20L, 0.5 GPM @ 57 PSIG, 4160 WATTS, 20 AMP BREAKER, 208V-1F-60.	INSTALL BELOW SINK
	WATER HEATER INSTANTANEOUS	¾"	½"	-	-	-	-	CHRONOMET INSTANT-FLOW #E-46L, 0.5 GPM @ 63 PSIG, 4600 WATTS, 20 AMP BREAKER, 208V-1F-60. (C.A SPEC)	
	WATER HEATER TANK TYPE	¾"	¾"	-	-	¾"	-	RHEEM WATER HEATER, MODEL NO. E6SP-6, 6 GALLON, 208V-1F-60, 3 KW AND 14.4 AMPS.	
	TRAP PRIMER	½"	-	-	-	-	-	PRECISION PLUMBING PRODUCTS TRAP PRIMER, MODEL NO. P-2, COPPER BODY, ADJUSTABLE WITH ½" COPPER TYPE "L" TO FLOOR DRAIN.	
	FLOOR DRAIN	-	-	2"	1½"	-	-	ZURN FLOOR DRAIN MODEL NO. 2-415-58, CAST IRON BODY, COMBINATION INVERTIBLE CLAMP AND ADJUSTABLE COLLAR, 2" BOTTOM OUTLET WITH 6" ROUND NICKEL BRONZE STRAINER.	WITH DEEP SEAL P-TRAP
	WATER HAMMER ARRESTER	-	-	-	-	-	-	SIUOX CHIEF 650 SERIES WATER HAMMER ARRESTER OR EQUAL, *SIZE & ZURN 2N-1446-BR #WH-201 STANDARD OR MANUFACTURER'S INSTRUCTION.	*
	WALL CLEANOUT	-	-	-	-	-	-	ZURN 2N-1446-BR #WH-201 STANDARD, BUT DURA-COATED CAST IRON BODY, GAS AND WATER TIGHT BRONZE PLUG AND STAINLESS STEEL WALL ACCESS COVER WITH SECURING SCREW.	
	FLOOR CLEANOUT	-	-	-	-	-	-	ZURN FLOOR CLEANOUT MODEL NO. 2N-1400 WITH GAS-TIGHT AND WATER-TIGHT TAPERED THREADED PLUG AND ROUND POLISHED NICKEL BRONZE SCORRIATED ADJUSTABLE TOP.	
	CLEANOUT	-	-	-	-	-	-	ZURN CLEANOUT FERRULE WITH PLUG #21440 WITH DURA-COATED CAST IRON BODY, WITH GAS-TIGHT AND WATER-TIGHT ASB TAPERED THREADED PLUG.	
	BREAK SINK	½"	¾"	2"	1½"	-	-	DAYTON D11219 SINGLE-BOWL-SINK (19" X 17" X 6½" BOWL) WITH ELKAY MODEL NO. LK02325 DUAL-HANDLE-GOOSNECK FAUCET	ACCESSIBLE TYPE
	STANDARD DRINKING FOUNTAIN	½"	-	2"	1½"	-	-	ELKAY SELF-CONTAINED, BARRIER-FREE, ELECTRIC, REFRIGERATED, WALL-MOUNTED, BI-LEVEL WATER COOLER/BOTTLE FILLING STATION #125126WLC, FURNISHED WITH PLUG-IN, 5-WIRE GROUNDING TYPE SERVICE CORD, STANDARD 120V, 60 HZ, 1PH, 120V RECEPTACLE REQUIRED, RATED AT 15 AMP MINIMUM, TO RECEIVE 3-WIRE PARALLEL BLADE GROUNDING TYPE MALE PLUG, PROVIDE CHROME SUPPLY STOP AND P-TRAP. SEE MANUFACTURER'S INSTRUCTIONS FOR PROPER INSTALLATION PER ACCESSIBILITY REQUIREMENTS.	ACCESSIBLE TYPE
	"ELEVATED" DRINKING FOUNTAIN (CHILLED)	½"	-	2"	1½"	-	-	HALSEY TAYLOR #OVL-H SEEP BI-LEVEL BARRIER FREE WATER-COOLER- PROVIDE CHROME SUPPLY STOP AND P-TRAP. FURNISH WITH #530-B REMOTE CHILLER. SEE MANUFACTURER'S INSTRUCTIONS FOR PROPER INSTALLATION PER ACCESSIBILITY REQUIREMENTS.	ACCESSIBLE TYPE
	DRINKING FOUNTAIN	½"	-	-	-	-	-	OASIS NAUTICA #POU1RHRS "HOT N° COLD" WATER-COOLER- PROVIDE CHROME SUPPLY STOP. SEE MANUFACTURER'S INSTRUCTIONS FOR PROPER INSTALLATION.	
	URINAL WALL MOUNTED	¾"	-	2"	1½"	-	-	KOHLER "BARBON SUPERIOR" URINAL MODEL NO. K-4960-EF FURNISH WITH #KHLER-K-15698 0.5 GPF FLUSH VALVE (OR ZURN #25738, 0.125 GPF, WHITE VITREOUS CHINA, WITH Z0660963E-FLUSHMETER VALVE)	0.5 GPF MAXIMUM ACCESSIBLE TYPE
	MOP SINK	½"	¾"	3"	1½"	-	-	FIAT MOP MOLDED STONE SERVICE BASIN MODEL NO. MSB-2424 WITH VINYL BUMPERGUARD, FURNISH WITH AMERICAN STANDARD FAUCET MODEL NO. 8344.112 WITH INTEGRAL VACUUM BREAKER AND STOPS, PROVIDE 42" RUBBER HOSE WITH FAUCET.	
	DRAIN PUMP BASIN	-	-	1½"	DISC 1½"	-	-	ZOELLER #131, FLOOR MOUNTED 5 GAL. POLYETHYLENE BASIN WITH CASKETED POLYETHYLENE LID, PUMP, ZOELLER #RPM-115V-1F-½ HP, 1725 RPM, 25 FT. HD. UL LISTED, PUMP-PASSES ¾" SPHERICAL SOLIDS, ELECTRICAL CONNECTION TO BE MADE WITH 15 FT. UL LISTED 3 WIRE-CORD-AND PLUG, BASIN AND PUMP TO BE TEMPERATURE RATED TO 150 °F. UNIT IS FURNISHED WITH CHECK VALVE, MODEL #10-0032-115V-15FT NORMALLY OPEN (N.O.) SINGLE PIGGYBACK FLOAT SWITCH, MODEL #10-0064-115V-15FT NORMALLY CLOSED (N.C.) SINGLE PIGGYBACK FLOAT SWITCH.	
	SOLENOID VALVE	-	-	-	-	-	-	OWNER SHALL PROVIDE ASCO RED HAT MODEL #821022-¾"NPT (TWO-WAY) NORMALLY CLOSED (N.C.) SOLENOID VALVE FOR EACH DEMO SINK. VALVE SHALL BE PROVIDED WITH 6 FT. UL LISTED 3 WIRE CORD AND PLUG, PLUMBING CONTRACTOR TO INSTALL.	
	THERMOSTATIC MIXING VALVE	-	-	-	-	-	-	STAMONS MIXING VALVE #7-225-C "MAXLINE", ½" INLETS AND OUTLET, THERMOSTATIC CONTROLLER WITH INTEGRAL CHECKS, ALL BRASS BODY WITH DUAL STAINLESS STEEL STRAINER, WOUND-RESISTANT TEMPERATURE ADJUSTMENT HANDLE, SET TO 109°. MOUNT IN ACCESSIBLE LOCATION.	

PLUMBING FIXTURE SCHEDULE-BBW	NTS	E 11/18/13
	42N-P0101-E00-SCHD	

	NEW WASTE OR SAN. SEWER		FLOOR CLEAN-OUT
	EXISTING WASTE OR SAN. SEWER		WALL CLEAN-OUT
	CONDENSATE DRAIN		FLOOR DRAIN
	GAS		VENT THRU ROOF
	NEW VENT		POINT OF CONNECTION
	EXISTING VENT		WATER METER
	NEW COLD WATER		SHUT-OFF VALVE
	EXISTING COLD WATER		CONCEALED SPRINKLER HEAD
	NEW HOT WATER		RECESSED PENDANT SPRINKLER HEAD
	EXISTING HOT WATER		UPRIGHT SPRINKLER HEAD
	PIPE DROP		PENDANT SPRINKLER HEAD BRASS FINISH
	PIPE RISE		
			PORTABLE FIRE EXTINGUISHER
			

FINISH:  
 B: BLACK  
 C: CHROME

## LEGEND AND SYMBOLS

<b>NTS</b>
<b>00N-P0101-D00-LGND</b>

D

04/03/15

LEGEND AND SYMBOLS	NTS	D 09/03/13
	00N-P0101-D00-LGND	


1. THESE PLANS MAY BE USED FOR CONSTRUCTION ONLY AFTER APPROVAL IS OBTAINED FROM THE BUILDING DEPARTMENT PLUMBING PLAN CHECK DIVISION AND THAT DIVISION'S STAMPED APPROVAL AND AUTHORIZED SIGNATURE APPEAR ON THE PLANS.
2. COORDINATE ALL WORK WITH ALL TRADES INCLUDED BUT NOT LIMITED TO ELECTRICAL, FIRE PROTECTION, MECHANICAL AND STRUCTURAL CONTRACTORS. INSTALL ALL WORK TO CLEAR NEW AND EXISTING ARCHITECTURAL AND STRUCTURAL MEMBERS. NO ITEM SUCH AS PIPE, DUCT, ETC. IS TO BE IN CONTACT WITH ANY EQUIPMENT.
3. REFER TO ARCHITECTURAL DRAWINGS FOR DEMOLITION WORK.
4. REFER TO ARCHITECTURAL DRAWINGS FOR EXACT FIXTURE LOCATION.
5. CONTRACTOR SHALL PROVIDE CUT SHEETS TO LSD&C FOR ALL EQUIPMENT AND DEVICES FURNISHED BY THE CONTRACTOR THAT DIVERT FROM SPECIFIED ITEM FOR REVIEW AND APPROVAL PRIOR TO THE PURCHASE OF ANY SUCH EQUIPMENT OR DEVICES.
6. THE PLUMBING CONTRACTOR SHALL BE RESPONSIBLE TO FIELD VERIFY THE EXACT LOCATIONS, SIZES, INVERTS AND CONDITION OF EXISTING SANITARY WASTE PIPING BELOW SLAB, VENT PIPING ABOVE CEILING AND UP THROUGH ROOF AND DOMESTIC COLD WATER SUPPLY PIPING TO TENANT'S DEWASED PREMISES PRIOR TO SUBMITTING HIS BID. NO ADDITIONAL COMPENSATION WILL BE MADE FOR ANY EXTRAS DUE TO CONTRACTOR'S FAILURE TO VISIT THE JOB SITE ANY/OR FAILURE TO PREDETERMINE ALL EXISTING CONDITIONS BEFORE SUBMITTING HIS BID.
7. ACCESS TO ALL COMPONENTS AND EQUIPMENT MUST BE PROVIDED TO MEET CODE AND SERVICE/MAINTENANCE EASE.
8. THE PLUMBING CONTRACTOR SHALL VERIFY WITH LOCAL CODES AS TO THE REQUIREMENT/INSTALLATION OF ANY "WATER SAVING" DEVICES TO THE FIXTURING FIXTURES. (EXAMPLE: TOILET, FAUCETS, ETC.).
9. PLUMBING SYSTEM SHALL BE PRESSURE TESTED AND STERILIZED PER LANDLORD'S CRITERIA AND LOCAL AUTHORITY.
10. UPON COMPLETION OF THE WORK, CONTRACTOR SHALL ENSURE THE PROPER WORKING ORDER OF THE SYSTEM(S) AND MAKE ANY ADJUSTMENTS AS REQUIRED.

<b>PLUMBING GENERAL NOTES</b>	<b>NTS</b>	<b>C</b> 04/03/15
	<b>00N-P0101-C00-NOTE</b>	

1. UNLESS OTHERWISE SPECIFIED, CONTRACTOR SHALL PROVIDE ALL NECESSARY EQUIPMENT, MATERIAL, LABOR AND SUPERVISION NECESSARY

1. TO COMPLETE THE PLUMBING WORK IN ACCORDANCE WITH THE SPECIFICATIONS AND STANDARDS.
2. FIELD VERIFY EXACT SIZE AND LOCATION OF EXISTING WASTE PIPING BELOW SLAB, VENT PIPING ABOVE CEILING AND UP THROUGH ROOF AND COLD WATER SUPPLY PIPING ABOVE CEILING PRIOR TO COMMENCEMENT OF ANY WORK. AFTER INSTALLATION AND FINAL CONNECTION OF NEW WASTE PIPING BELOW SLAB, BACK FILL AND PATCH IN ACCORDANCE WITH THE LANDLORD'S CRITERIA REGARDING SUCH WORK.
3. CONTRACTOR SHALL FURNISH AND INSTALL ALL OF THE NECESSARY PLUMBING FIXTURES (SEE PLUMBING RESPONSIBILITY SCHEDULE ON THIS SHEET) TO SERVE THE TENANT'S DEMISED PREMISES AND MAKE NECESSARY INSTALLATION OF DOMESTIC WATER AND SEWER PIPING FROM TENANT'S DEMISED PREMISE TO CONNECTION PROVIDED BY LANDLORD.
4. SANITARY VENTS SHALL BE ROUTED TO THE EXISTING LANDLORD'S POINT OF CONNECTION WITHIN THE TENANT'S DEMISED PREMISES OR TO A POINT APPROVED BY LOCAL AUTHORITY. THE CONTRACTOR SHALL PROVIDE A CAPPED TIE FOR POSSIBLE FUTURE CONNECTION (IF REQUIRED BY LANDLORD). CONTRACTOR SHALL COORDINATE ALL ROOF PENETRATIONS WITH THE LANDLORD'S ROOFING CONTRACTOR, AS REQUIRED. VENT THRU ROOF SHALL BE AT LEAST 15 FEET AHEAD FROM A/C UNIT FRESH AIR INTAKE.
5. SEAL AROUND ALL PIPES PENETRATING FIRE SEPARATIONS WITH LISTED AND APPROVED FIRE SEAL MATERIAL. ONLY LISTED AND APPROVED SEALANTS AND METHODS FOR THE SPECIFIC USE WILL BE PERMITTED.
6. THE CONTRACTOR SHALL INSTALL ALL TOILET FIXTURES IN ACCORDANCE WITH ALL CODES AND AS REQUIRED BY LANDLORD'S CRITERIA. CONTROLS FOR FLUSH VALVES SHALL BE MOUNTED ON THE WIDE SIDE OF THE WATER CLOSET AND NO MORE THAN 44" A.F.F.
7. THE CONTRACTOR SHALL ENSURE THAT ALL SLAB PENETRATIONS WITHIN THE TENANT'S DEMISED PREMISES ARE PROPERLY SEALED AND REMAIN WATERIGHT TO PREVENT ANY POSSIBLE DAMAGE TO OTHER TENANTS AND/OR TO THE BUILDING. FAILURE TO DO SO SHALL BE AT THE RISK AND SOLE EXPENSE OF THE CONTRACTOR.
8. ALL MATERIAL SHALL BE NEW AND OF COMMERCIAL GRADE, AND BEAR UNDERWRITER'S LABORATORIES AND UNION LABELS WHERE SUCH LABELING APPLIES.
9. PLUMBING CONTRACTOR MUST FIELD VERIFY PROPER SLOPE OF EXISTING SEWER TO MAIN SEWER PRIOR TO ANY NEW PLUMBING INSTALLATION.
10. PLUMBING CONTRACTOR MUST VISIT THE JOBSITE TO BECOME FAMILIAR WITH MAJOR ITEMS SUCH AS STRUCTURAL ELEMENTS AND OTHER EXISTING JOB CONDITIONS THAT MAY AFFECT THE WORK. ADDITIONALLY, PLUMBING CONTRACTOR SHALL VERIFY EXACT LOCATIONS AND DIMENSIONS OF SUCH ITEMS AS WASTE, VENTS, WATER LINES, ETC.
11. PLUMBING CONTRACTOR TO FAMILIARIZE AND FOLLOW SPECIFICATIONS AND DETAILS CONTAINED IN DESIGN CRITERIA OF TENANT HANDBOOK.
12. PLUMBING CONTRACTOR TO CLEAR ALL EXISTING AND NEW DRAIN LINES AND FIXTURES, PRIOR TO TURNING OVER SPACE TO TENANT.
13. PLUMBING CONTRACTOR SHALL PROVIDE ACCESS TO VALVES, TRAP PRIMERS, ETC. INSTALLED BEHIND WALLS, FLOORS OR CEILINGS.
14. NO P/Vc PLASTIC PIPING ALLOWED WITHIN CEILING VOIDS USED FOR NON-DUCTED RETURN AIR PLENUM OR IN WALLS, EXCEPT IN CANADA WHERE XFR-P/Vc MAY BE USED IF PERMITTED BY THE AUTHORITY HAVING JURISDICTION.
15. THE GENERAL CONTRACTOR'S FIRE SPRINKLER SUB-CONTRACTOR SHALL DESIGN AND INSTALL FIRE SPRINKLER SYSTEM CONFORMING TO LANDLORD'S CRITERIA, TENANT'S REQUIREMENTS, AND REF. LOCAL CODES AND NFPA STANDARDS.

<p>THIS SET IS PART OF THE CONSTRUCTION DOCUMENTS, OTHER SHEETS INCLUDING PLANS, DETAILS AND SPECIFICATIONS APPLY. THAT SHOWN HEREON IS SCHEMATIC IN NATURE AND NOT TO BE USED AS A SHOP DRAWING. THEREFORE, INCLUDE ALL MODIFICATIONS REQUIRED TO CONFORM TO SITE CONDITIONS AND THE EQUIPMENT AND MATERIAL USED. VERIFY LOCATION AND DIMENSIONS OF ALL ARCHITECTURAL AND STRUCTURAL ELEMENTS AS SHOWN ON THEIR RESPECTIVE DOCUMENTS. THESE ELEMENTS ARE SHOWN FOR REFERENCE AND SHALL BE VERIFIED PRIOR TO CONSTRUCTION AND THE ENGINEER ASSUES NO LIABILITY FOR THE ACCURACY OF THESE ELEMENTS. NO DESIGN RESPONSIBILITY IS ASSUMED FOR ANY PORTION OF THE WORK THAT THE PROFESSIONAL ENGINEER HAS NOT SIGNED AND SEALED PER STATE OR PROVINCE REQUIREMENTS.</p>	<p style="text-align: center;"><b>NTS</b></p> <p style="text-align: center;"><b>00N-P0101-A00-NOTE</b></p>
---	--

 **LARSON BINKLEY**

Larson Binkley, Inc.  
310 W 20th Street, Suite 200  
Kansas City, Missouri 64108

T 816-997-9601  
F 816-997-9602  
[larsonbinkley.com](http://larsonbinkley.com)

**Limited**brands

LIMITED STORE PLANNING, INC.  
d/b/a STORE DESIGN & CONSTRUCTION  
Three Limited Parkway • Columbus, Ohio 43230  
Telephone: 614.415.7000 • Fax: 614.415.7349

PROJECT INFORMATION:		024200396	
<b>BATH &amp; BODY WORKS</b> <b>MEMORIAL CITY MALL</b> 303 MEMORIAL CITY WAY SUITE 733 HOUSTON, TX 77024			
SCORE:	RELO DWIN / NEW	PACKAGE:	1
DESIGN TYPE:	EASTON-G	GENERATION:	14150
LSMC PROJECT #:	60695	A/E PROJECT #:	13643

REVISIONS:		
	REQUIRED BY:	DATE
1	STOREFRONT REVISION - REV 1	6/10/2011
2	REVISION 2 - L.L. / PERMIT COMMENTS	6/27/2011

ELITE CONSTRUCTION GROUP  
LAKE JACKSON, TX  
PHONE: 979-285-0712  
NOTE: THESE PRINTS HAVE BEEN  
REDUCED BY 50 PERCENT. SCALE  
WILL BE 50 PERCENT OF WHAT IS  
NOTED ON PLANS

DATE ISSUED: 04/11/2014  
DESIGNED BY: JES  
DRAWN BY: JES  
CHECKED BY: NRP

## PLUMBING NOTES AND SCHEDULES

DRAWING NUMBER:  
P01.01