QTY.	NO.	LOCATION	SIZE (NOMINAL) width x height x thickness	DOOR MATERIAL	FRAME	RATING	HDWARE GROUP	DETAIL NUMBER HEAD	DETAIL NUMBER JAMB	DETAIL NUMBER SILL	REMARKS / NOTES
1	①	GLASS WALL SYSTEM	26'-0" x 9'-6" ⚠1	1/2" TEMP. GLASS	METAL	NONE	A1	A A08.3	A A08.6	A A08.3	PRE-FINISHED BY MFG
1	②	SALES/NON-SALES	3'-6" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	-	B1	R A12.2	R A12.2	D A12.2	-
1	③	CORRIDOR/NON-SALES	3'-6" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	-	B1	F A12.2	F A12.2	- -	-
1	④	TOILET ROOM	3'-0" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	-	C1	F A12.2	F A12.2	G A12.2	-
1	⑤	REAR SERVICE	3'-6" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	45 MIN.	F	N A12.2	N A12.2	E A12.2	RATING AS REQD BY CODE
1	⑥	CLOSET	2'-0" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	-	B4	F A12.2	F A12.2	D A12.2	-
1	⑦	CLOSET	3'-6" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	-	B4	R A12.2	R A12.2	D A12.2	-
1	⑧	CLOSET	3'-0" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	-	B4	R A12.2	R A12.2	D A12.2	-
-	⑨	OFFICE DOOR	3'-0" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	-	D	F A12.2	F A12.2	- -	-
-	⑩	BLIND DOOR	2'-0" x 7'-0" x 1 3/4"	S.C. WOOD	WOOD	-	G1	1/1 A12.2	1/1 A12.2	- -	-
-	⑪	OPERABLE DISPLAY	X'-X" x X'-X" (93"x75"MAX.)	GLASS	ALUMINUM	-	H	A08.5	A08.5	A08.6	BY KAWNEER SERIES 190
-	⑫	REMOTE SERVICE	3'-0" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	-	K	- -	- -	F A12.2	
-	⑬	SLIDING GRILLE	X'-X" x X'-X"	METAL	METAL	NONE	A8	- -	- -	- -	W/ 3'-0" x 7'-0" EGRESS DOOR AS REQD BY CODE
-	⑭	SLIDING POCKET DOOR	X'-X" x X'-X" x 1 3/4"	WOOD	-	NONE	J	- -	- -	- -	
-	⑮	MOP CLOSET	2'-0" x 7'-0" x 1 3/4"	HOLLOW METAL	HOLLOW METAL	-	E1	L2 A12.2	L1 A12.2	- -	-

DOOR NOTES

1. UNLESS NOTED OTHERWISE, GENERAL CONTRACTOR TO PAINT ALL DOORS ON SALES FLOOR PT-1 SEMI-GLOSS, AND DOORS IN NON-SALES PT-5 SEMI-GLOSS.

HARDWARE NOTES

1. DOOR HARDWARE SHALL BE OF THE LEVER OR PUSH TYPE, MOUNTED 30" TO 44" ABOVE FINISH FLOOR. FINISH SHALL BE STAINLESS STEEL AT ALL LOCATIONS. ALL DOOR HARDWARE SHALL COMPLY WITH FEDERAL AND STATE ACCESSIBILITY REQUIREMENTS.
2. ALL EXIT DOORS TO BE OPERABLE FROM INSIDE WITHOUT USE OF A KEY, SPECIAL KNOWLEDGE OR EFFORT.
3. THE FORCE REQUIRED TO OPERATE ANY DOOR SHALL BE MAXIMUM 5 LBS. FOR EXTERIOR DOORS AND INTERIOR DOORS.
4. ALL LOCKING HARDWARE MUST INCLUDE 'U-CHANGE' LOCK CYLINDERS. ALL DOORS TO BE KEYED ALIKE UNLESS NOTED OTHERWISE.

GENERAL NOTES

1. DOORS AT STOREFRONT TO HAVE SIGN WITH 1" CONTRASTING LETTERING ABOVE DOORS STATING "THESE DOORS TO REMAIN IN FULL OPEN POSITION DURING BUSINESS HOURS" ⚠2
2. EXIT DOORS TO BE OPERABLE FROM THE INSIDE WITHOUT THE USE OF A KEY OR ANY SPECIAL KNOWLEDGE OR EFFORT.
3. DOORS WITHIN THE PATH OF TRAVEL FOR ACCESSIBILITY TO BE OPERABLE WITH A SINGLE EFFORT BY LEVER, PANIC BAR OR PUSH/PULL HARDWARE.
4. DOOR HARDWARE SHALL BE OF THE LEVER OR PUSH TYPE MOUNTED 30" TO 44" ABOVE THE FLOOR AND SHALL BE OPERABLE WITH A MAXIMUM EFFORT OF 5 LBS. FOR INTERIOR DOORS AND EXTERIOR DOORS.
5. THRESHOLDS SHALL NOT EXCEED 1/2" IN HEIGHT. RAISED THRESHOLDS AND FLOOR LEVEL CHANGES AT ACCESSIBLE DOORWAYS SHALL BE BEVELED WITH A SLOPE NO GREATER THAN 1:2.
6. ALL COMPONENTS OF FIRED RATED DOOR ASSEMBLIES SHALL BEAR THE LABEL OF AN APPROVED TESTING AGENCY.
7. BOTH DOORS SHALL BE FINISHED THE SAME UNLESS OTHERWISE NOTED.
8. ALL WOOD DOORS, FRAMES AND TRIM SHALL BE A.W.I. OR W.I.C. CUSTOM GRADE.
9. REFER TO MECHANICAL PLAN FOR ANY REQUIRED UNDERCUTS FOR AIR TRANSFER.

HARDWARE GROUPS

⚠1 **"A1"** SLIDING GLAZED WALL PANELS:
DOOR IS SUPPLIED AND INSTALLED BY GLAZING CONTRACTOR.

DOOR HARDWARE AS MANUFACTURED BY NANAWALL., INC. SERIES HSW75, TOP TRACK ONLY, TOP AND BOTTOM RAILS, BRUSHED STAINLESS STEEL FINISH. CONTACT: DAVE KIRSCHBAUM (PH: 330-283-9392) (ALTERNATE CR LAURENCE, CO. INC. SERIES 5512)

HARDWARE:
DOOR SYSTEM TO RECEIVE (1) FOOT OPERATION TYPE BRUSHED STAINLESS STEEL FLOOR PIN AT EACH END. G.C. TO INSTALL U-CHANGE CYLINDER LOCKSET IN PRE-DRILLED HOLES OF SLIDING DOOR BASE, BRUSHED STAINLESS STEEL THUMB TURN ON TENANT SIDE.
VERIFY ALL HARDWARE WITH OWNER APPROVED SHOP DRAWINGS.

INSTALLATION:
REFER TO HORIZONTAL SLIDING DOOR SPECIFICATIONS ON SHEET A15.2, SECTION 081010 FOR ADDITIONAL INFORMATION/INSTALLATION INSTRUCTIONS.

~~INTERIOR FRAMELESS ENTRANCE DOORS: SINGLE ACTING 1/2" TEMPERED GLASS DOOR, VISTAWALL GLASS SYSTEMS, (972) 551-6100, (OR OWNER APPROVED EQUAL). ALL GLAZING CHANNELS, RAILS AND DOOR~~
~~**"A2"** HARDWARE SHALL BE BRUSHED STAINLESS STEEL FINISH.~~
~~HARDWARE (GLAZING CONTRACTOR TO SUPPLY AND INSTALL):~~
- ~~1 EA. TOP PIVOT: DORMA PT 10 CENTER HUNG~~
- ~~1 EA. BOTTOM PIVOT: DORMA PT 10 CENTER HUNG~~
- ~~1 EA. DEADBOLT: RYADON EL05 WITH 11-5DT01 THUMBTURN~~
- ~~1 EA. CYLINDER: U-CHANGE #3MAKEMAID2 WITH 626 FINISH. PHONE: (888) 541-1300, "TEAM FOXTROT"~~
- ~~1 EA. PULLS: CR LAURENCE 2ALP00 - 24" PULL~~
- ~~2 EA. DUSTPROOF STRIKES: ASSA #MNIVRD25F2 32D FLUSH MOUNTED IN FLOOR. COORDINATE OPEN LOCATION WITH OWNER~~
- ~~1 EA. DOOR HEAD: VISTAWALL F6 1128 HEADER & VISTAWALL F6 1129 FILLER~~

~~EXISTING ENTRANCE DOORS:~~
~~HARDWARE:~~
~~**"A4"**~~
- ~~HINGES: REPLACE WITH NON-REMOVABLE PIN HINGES~~
- ~~LOCKSET: REPLACE WITH U-CHANGE. PHONE: (888) 541-1300, "TEAM FOXTROT"~~
- ~~DOOR HOLDERS: INSTALL IVES FS452-5-B26D AT EACH LEAF~~
- ~~MISCELLANEOUS: REPLACE WEATHERSTRIPPING AND THRESHOLD AS REQUIRED~~

~~SLIDING GRILLE:~~
- ~~DAGENDOR~~
~~**"A8"**~~
- ~~MODEL "SUPRA"~~
- ~~LEAD POST - COMPLETE WITH TOP AND BOTTOM LOCKING BOLTS & SECURITY FLAP~~
- ~~END POST - COMPLETE WITH TOP AND BOTTOM LOCKING BOLTS~~
- ~~TRACK - EXTRUDED ALUMINUM 1 3/8" X 1 1/2", CURVED TRACK SHALL BE SUPPLIED WITH 18" STANDARD RADIUS.~~
- ~~EGRESS DOOR REQUIRED - SUPPLIED WITH HARDWARE 3'-0" X 7'-0" OPENING~~
- ~~FINISH - CLEAR ANODIZED~~
- ~~G.C. TO COORD WITH MANUFACTURER'S RECOMMENDATIONS CONCERNING INSTALLATION AND REQUIRED SUPPORT FOR SLIDING GRILLE. G.C. TO CONTACT~~
~~LSD & C PURCHASING AGENT AND MANUFACTURER @ 1-800-301-0877 BEFORE PROCEEDING WITH PLACING ANY ORDER TO GUARANTEE PROPER FIT. DOOR TO BE SUPPLIED WITH GENERIC FACTORY INSTALLED LOCK CYLINDER TO BE REPLACED WITH OWNER SUPPLIED HEDECO LOCK CYLINDER PRIOR TO TURNOVER.~~

SALES/NON-SALES DOOR OR NON-PUBLIC HALLWAY/NON-SALES DOOR:
HARDWARE:
"B1"
- 1 1/2 PR HINGES: STANLEY FI79-26D
- 1 EA PUSH PLATE: IVES 8200-B26D-4"X16"
- 1 EA PULL PLATE: IVES 8302-8-B26D-4"X16"
- 1 EA CLOSER: CORBIN RUSSWIN DC3200-M82-689 (MOUNT ON NON-SALES SIDE)
- 1 EA KICKPLATE: IVES 8400-B26D-10" X DOOR WIDTH MINUS 2"
- 1 EA DOOR HOLDER: (AT NON-RATED DOORS) IVES FS446-B26D
- 1 EA LATCHSET: (AT RATED DOORS) CORBIN RUSSWIN CL3310-NZD-626
- 1 EA SMOKE SEAL: (AT RATED DOORS) PEMKO S88W

PUBLIC HALLWAY/NON-SALES DOOR:
HARDWARE:
"B2"
- ~~1 1/2 PR HINGES: STANLEY FI79-26D~~
- ~~1 EA LATCHSET: U-CHANGE #5L152NB602 WITH RHODES STYLE LEVER AND 626 FINISH. (SPECIFY DOOR HANDING WHEN ORDERING) PHONE: (888) 541-1300, "TEAM FOXTROT"~~
- ~~1 EA CLOSER: CORBIN RUSSWIN DC3200-M82-689 (MOUNT ON NON-SALES SIDE)~~
- ~~1 EA KICKPLATE: IVES 8400-B26D-10" X DOOR WIDTH MINUS 2"~~
- ~~1 EA DOOR HOLDER: (AT NON-RATED DOORS) IVES FS446-B26D~~
- ~~1 EA SMOKE SEAL: (AT RATED DOORS) PEMKO S88W~~

~~REMOTE STOCKROOM DOOR:~~
~~HARDWARE:~~
~~**"B3"**~~
- ~~1 1/2 PR HINGES: STANLEY FI79-26D WITH NON-REMOVABLE PIN~~
- ~~1 EA LATCHSET: U-CHANGE #5L152NB602 WITH RHODES STYLE LEVER AND 626 FINISH. (SPECIFY DOOR HANDING WHEN ORDERING) PHONE: (888) 541-1300, "TEAM FOXTROT"~~
- ~~1 EA CLOSER: CORBIN RUSSWIN DC3200-M82-689 (MOUNT ON NON-SALES SIDE)~~
- ~~1 EA KICKPLATE: IVES 8400-B26D-10" X DOOR WIDTH MINUS 2"~~
- ~~1 EA DOOR HOLDER: (AT NON-RATED DOORS) IVES FS446-B26D~~
- ~~1 EA SMOKE SEAL: (AT RATED DOORS) PEMKO S88W~~

NON-PUBLIC HALLWAY/CLOSET DOOR:
HARDWARE:
"B4"
- 1 1/2 PR HINGES: STANLEY FI79-26D
- 1 EA LATCHSET: CORBIN RUSSWIN CL3357-NZD-626
- 1 EA DOOR STOP: IVES WS402-B26D
- 1 FLUSHBOLT: IVES 43, 26D 12" (AT TOP OF INACTIVE LEAF OF DOUBLE DOOR)

TOILET ROOM DOOR: UNFINISHED HOLLOW METAL DOOR & FRAME
HARDWARE:
"C1"
- 1 1/2 PR HINGES: STANLEY FI79-26D
- 1 EA LATCHSET: CORBIN RUSSWIN CL3320-NZD-626
- 1 EA KICKPLATE: IVES 8400-B26D-10"X34"
- 1 EA DOOR STOP: IVES WS402-B26D
- 1 EA HOOK: ROCKWOOD 806-B26D CENTERED ON DOOR AT 72" AFF
- 1 EA CLOSER: (AT RATED DOORS) CORBIN RUSSWIN DC3200-M82-689 (MOUNT ON TOILET ROOM SIDE)
- 1 EA SMOKE SEAL: (AT RATED DOORS) PEMKO S88W

~~**"D2"** ELEVATED TOILET ROOM DOOR:~~
~~HARDWARE:~~
- ~~2 PR HINGES: STANLEY (CEHM-(92) 4 1/4" X 4 1/2" (OWNER PROVIDED)~~
- ~~1 EA LATCHSET: NANZ 2012 LEVER HANDLE 5 1/2" L, W/ 5000 ROSETTE. FURNISHED BY OWNER.~~
- ~~1 EA DOOR STOP: IVES WS402-B26D~~
- ~~1 EA HOOK: ROCKWOOD 806-B26D CENTERED ON DOOR AT 72" AFF~~
- ~~1 EA CLOSER: CORBIN RUSSWIN DC3200-M82-689~~
- ~~1 EA KICKPLATE: IVES 8400-B26D-10" X DOOR WIDTH MINUS 2"~~
- ~~1 EA SMOKE SEAL: (AT RATED DOOR) PEMKO S88W~~

~~**"D"** OFFICE DOOR:~~
~~HARDWARE:~~
- ~~1 1/2 PR HINGES: STANLEY FI79-26D WITH NON-REMOVABLE PIN~~
- ~~1 EA LATCHSET: U-CHANGE #5L152NB602 WITH RHODES STYLE LEVER AND 626 FINISH. (SPECIFY DOOR HANDING WHEN ORDERING) PHONE: (888) 541-1300, "TEAM FOXTROT"~~
- ~~1 EA KICKPLATE: IVES 8400-B26D-10" X DOOR WIDTH MINUS 2"~~
- ~~1 EA DOOR HOLDER: IVES FS446-B26D~~
- ~~1 EA SMOKE SEAL: (AT RATED DOOR) PEMKO S88W~~
- ~~1 EA MAGNETIC HOLD OPEN: GLYNN JOHNSON #LEH-U24D~~

~~**"E1"** MOP SINK/CLOSET DOOR:~~
~~HARDWARE:~~
- ~~1 1/2 PR HINGES: STANLEY FI79-26D~~
- ~~1 EA LATCHSET: CORBIN RUSSWIN CL3357-NZD-626~~
- ~~1 EA KICKPLATE: IVES 8400-B26D-10" X DOOR WIDTH MINUS 2"~~
- ~~1 EA DOOR STOP: IVES WS402-B26D~~
- ~~1 EA HOOK: ROCKWOOD 806-B26D CENTERED ON DOOR AT 72" AFF~~

~~**"E2"** ELEVATED MOP SINK DOOR: HOLLOW METAL DOOR WITH 1/4" VENEER AND HARD WOOD TRIMS APPLIED~~
~~HARDWARE:~~
- ~~1 1/2 PR HINGES: STANLEY FI79-26D~~
- ~~1 EA LATCHSET: NANZ 2012 LEVER HANDLE 5 1/2" L, W/ 5000 ROSETTE. FURNISHED BY OWNER.~~
- ~~1 EA DOOR STOP: IVES WS402-B26D~~
- ~~1 EA HOOK: ROCKWOOD 806-B26D CENTERED ON INSIDE OF DOOR AT 72" AFF~~
- ~~1 EA DEADBOLT: CORBIN RUSSWIN SARGENT 407, CHROME SATIN FINISH (MOUNT AT 36" AFF)~~
- ~~1 EA CYLINDER: U-CHANGE #3MAKEMAID2 WITH 626 FINISH. PHONE: (888) 541-1300, "TEAM FOXTROT"~~

"F" SERVICE DOOR:
HARDWARE:
- 3 PR HINGES W/SECURITY STUDS BY G.C.: IVES 5BB1SH
- 1 EA PANIC HARDWARE: TRIDENT TEL-210 (SUPPLIED BY OWNER, INSTALLED BY G.C.) WITH U-CHANGE CYLINDER. MOUNT AT 45" AFF OR AS REQUIRED BY CODE
- 1 EA CLOSER: CORBIN RUSSWIN DC3210-M82-689
- 1 EA KICKPLATE: IVES 8400-B26D-10" X DOOR WIDTH MINUS 2"
- 1 EA VIEWER: IVES U698-B26D CENTERED ON DOOR AT 54"
- 1 EA LOCK PROTECTOR: GLYNN JOHNSON #LPI-U532D
- 1 EA DOOR SWEEP: (AT EXTERIOR LOCATION) PEMKO 216AV
- 1 EA DOOR SEAL: (AT EXTERIOR OR RATED DOORS) PEMKO S88W
- 1 EA THRESHOLD: (AT EXTERIOR LOCATION) PEMKO 270A
- 1 EA DOOR CONTACT: (AT EXTERIOR LOCATION) INSTALLED BY OWNER
- 1 EA SIGN PLAQUE: BY OWNER

AT EXISTING SERVICE DOORS, PROVIDE AND INSTALL HARDWARE AS NEEDED TO MEET THE ABOVE REQUIREMENTS. ALSO REMOVE OUTSIDE LEVER/LOCK AND INSTALL BLANK COVER PLATES TO CONCEAL HOLES AND PAINT ENTIRE DOOR PER MALL'S REQUIREMENTS.

ALL DOORS TO RECEIVE PANIC HARDWARE AS SPECIFIED ABOVE.

"G1" ~~BLIND DOORS (SALES):~~
~~HARDWARE:~~
- ~~1 1/2 PAIR HINGES PER LEAF - STANLEY FI79-26D~~
- ~~1 EA DEADBOLT: CORBIN RUSSWIN DL2111, 626 (MOUNT AT 36" AFF)~~
- ~~1 EA PULL: DALDWIN - FLUSH RING PULL - 8375.264 - SATIN CHROME (MOUNT AT 42" AFF)~~
- ~~1 EA ROLLER CATCH: IVES 336, 26D~~
- ~~1 FLUSHBOLT: IVES 43, 26D 12" (AT TOP OF INACTIVE LEAF OF DOUBLE DOOR)~~

"G2" ~~BLIND DOORS (NON-SALES):~~
~~HARDWARE:~~
- ~~1 EA HINGE: FULL HEIGHT HEAVY DUTY PIANO HINGE, 26D~~
- ~~1 EA DEADBOLT: CORBIN RUSSWIN DL2111, 626 (MOUNT AT 36" AFF)~~
- ~~1 EA WIRE PULL: IVES 36, 26D 4" (MOUNT AT 42" AFF)~~
- ~~1 EA ROLLER CATCH: IVES 336, 26D~~
- ~~1 EA DOOR STOP: IVES WS402-B26D~~

"H" ~~OPERABLE DISPLAY WINDOW: ALUMINUM FRAMED DOOR WITH 1/4" TEMPERED GLASS. KAWNEER 190 NARROW STILE WITH BEVELED STOP. 2 1/2" STILE, 2 1/4" TOP AND BOTTOM RAILS. FINISH TO MATCH KAWNEER "INTERPON D2000 BONE WHITE"~~
~~HARDWARE:~~
- ~~1 EA HINGE: ROTON FULL HEIGHT ALUMINUM HINGE, CLEAR ANODIZED FINISH~~
- ~~1 EA LOCKSET: STANDARD KAWNEER LOCKSET W/ 26D FINISH. MOUNT 44" AFF. ALL DOORS TO BE KEYED ALIKE.~~

"J" ~~SLIDING GRILLE POCKET DOOR (SALES):~~
~~HARDWARE:~~
- ~~1 EA HINGE: FULL HEIGHT HEAVY DUTY PIANO HINGE, 26D~~
- ~~1 EA PULL: IVES 426, 26D (MOUNT AT 42" AFF)~~
- ~~2 EA MAGNETIC CATCH (1 CATCH AT 2" AT 84" - 1 CATCH AT 0" AFF)~~
- ~~0" METAL KICK PLATED INSTALLED AT BASE OF DOOR. FINISHED 14" x 2"~~
- ~~1 EA DEADBOLT: CORBIN RUSSWIN DL2111, 626 (MOUNT AT 36" AFF)~~

"K" ~~REMOTE STORAGE DOOR (SERVICE DOOR):~~
~~HARDWARE:~~
- ~~3 PR HINGES W/SECURITY STUDS BY G.C.: IVES 5BB1SH~~
- ~~1 EA LOCKSET:~~
~~U.S. STORES: INSTALL SIMPLEX KEYPAD LEVER LOCK SERIES L1000 MODEL 1021A 26D PROVIDED AND INSTALLED BY G.C. - ORDER THRU 1-888-541-1300, "TEAM FOXTROT"~~
~~CANADA STORES: INSTALL U-CHANGE CYLINDER LOCK W/ THUMB TURN ON INSIDE. ORDER THRU 1-888-541-1300, "TEAM FOXTROT"~~
- ~~1 EA CLOSER: CORBIN RUSSWIN DC3210-M82-689~~
- ~~1 EA KICKPLATE: IVES 8400-B26D-10" X DOOR WIDTH MINUS 2"~~
- ~~1 EA VIEWER: IVES U698-B26D CENTERED ON DOOR AT 54"~~
- ~~1 EA LOCK PROTECTOR: GLYNN JOHNSON #LPI-U532D~~
- ~~1 EA DOOR SWEEP: (AT EXTERIOR LOCATION) PEMKO 216AV~~
- ~~1 EA DOOR SEAL: (AT EXTERIOR OR RATED DOORS) PEMKO S88W~~
- ~~1 EA THRESHOLD: (AT EXTERIOR LOCATION) PEMKO 270A~~
- ~~1 EA DOOR CONTACT: (AT EXTERIOR LOCATION) INSTALLED BY OWNER~~
- ~~1 EA SIGN PLAQUE: BY OWNER~~

~~AT EXISTING SERVICE DOORS, PROVIDE AND INSTALL HARDWARE AS NEEDED TO MEET THE ABOVE REQUIREMENTS. ALSO REMOVE OUTSIDE LEVER/LOCK AND INSTALL BLANK COVER PLATES TO CONCEAL HOLES AND PAINT ENTIRE DOOR PER MALL'S REQUIREMENTS.~~
~~ALL DOORS TO RECEIVE PANIC HARDWARE AS SPECIFIED ABOVE~~

DOOR SCHEDULE

N.T.S. | 42S-A002-J00-SCHE | J | 10.14.11

CODE	MATERIAL	MANUFACTURER	DESCRIPTION	LOCATION / NOTES
	PAINT FINISHES			
PT-1	PAINT	BENJAMIN MOORE	NO. 844 - "ALOE VERA"	SATIN IMPERVO # 314 AT WALLS, FLAT AT CEILING & REGAL AQUA GLO SEMI-GLOSS AT TRIM/BASE UNLESS NOTED OTHERWISE
PT-5	PAINT	BENJAMIN MOORE	NO. 876 - "WHITE"	NON-SALES, CORRIDORS, & DOORS; SATIN FINISH AT WALLS, FLAT AT CEILINGS
PT-11	VARNISH	GREEN DOLPHIN	FIRE SAFE 108 WOOD INTUMESCENT FIRE RETARDANT WOOD TREATMENT	FOR USE WITH SF-2 & NON-SALES SHELVING (WHEN REQD)
PT-12	PAINT	BENJAMIN MOORE	NO. 0062 - "BABY'S BREATH"	EXTERIOR GRADE BOARD & INTERIOR OF ILLUMINATED TRANSOM; HIGH GLOSS
PT-13	PAINT	BENJAMIN MOORE	NO. OC-5 - "MARITIME WHITE"	FLAT AT TOILET ROOM CEILING SATIN AT TOILET ROOM DOOR JAMB REVEALS
PT-15	PAINT	BENJAMIN MOORE	NO. 2130-20 - "DEEP CAVIAR"	BACK WALL OF BACKWRAP VIDEO MONITOR DISPLAY (DOMESTIC)
PT-16	PAINT	BENJAMIN MOORE	TO MATCH PANTONE #294 (SEMIGLOSS)	WALL ABOVE BREAK AREA BAR COUNTER
PT-17	PAINT	SHERWIN WILLIAMS	NO. 2065-20 "DARK ROYAL BLUE" (SATIN)	STANDARD BARRICADE
	FLOOR COVERINGS			
FC-4	VINYL COMPOSITE TILE	ARMSTRONG	EXCELON NO. 51901 - "TAUPE", IMPERIAL TEXTURE	NON-SALES FLOOR
FC-5	VINYL COMPOSITE TILE	ARMSTRONG	EXCELON NO. 51816 - "CHERRY RED", IMPERIAL TEXTURE	NON-SALES FIRE LANE, IN FRONT OF ELECTRICAL PANELS
~~FC-12~~	~~PORCELAIN~~	~~INNOVATIVE MARBLE AND TILE INC.~~	~~ABIDKO, ROVERE 7 5/8" X 35" X 7/16" WITH 1/16" GROUT JOINTS~~	~~SALES AREA FLOOR~~
FC-13	VINYL COMPOSITE TILE	ARMSTRONG	EXCELON NO. 51869 - "HUMMUS" IMPERIAL TEXTURE	NON-SALES PROCESSING AREA ONLY
~~FC-14~~	~~WALK OFF MAT~~	~~MATHORKS 301 837 1272~~	~~DESIGNER LINKS "SAFARI" CARPET W/ TACFAST BACKING IN DARK BROWN. PVC GRATE~~ ~~CALL (301) 837 1272~~	~~INTERIOR WALK OFF MAT FOR EXTERIOR STORES~~
FC-18	PORCELAIN TILE	CROSSVILLE	"CHESTNUT" - 6" X 24" X 3/8" & 6" X 36" X 3/8" TILE W/ 1/16" GROUT JOINT	PACKAGE I SALES AREA; RANDOM PATTERN FROM SIDE TO SIDE OF STORE
FC-19	TILE	VINE STREET TILE STUDIOS	SICILIAN WHITE TILE 13"X13"	TOILET ROOM
~~FC-20~~	~~CERAMIC TILE~~	~~CAESAR CERAMICS~~	~~24" X 24" ABSOLUTE PORCELAIN TILE "WHITE STAR" - LAPPATO HONED FINISH. FIELD CUT WITH CONCEALED EDGES~~	~~EXTERIOR STOREFRONT BASE~~
B-1	VINYL BASE	ARMSTRONG	NO. 03 - "BISQUEWARE", 4" HIGH (6" AT TOILET ROOM)	NON-SALES & CORRIDOR
~~B-2~~	~~WOOD BASE~~	~~L.T. CUSTOM FIXTURES~~	~~4" HIGH OAK WOOD BASE - FIELD VERIFY~~	~~PASS THRU AND FISCAL LOCATIONS AS SPECIFIED~~
B-3	WOOD BASE		PAINT GRADE POPLAR	PAINT PT-1, U.O.N.
B-5	WOOD BASE	L.T. CUSTOM FIXTURES	4" HIGH OAK WOOD BASE (TRANSVERSE GRAIN)	UNIT 5B, PASS THRU PORTAL, & CONCIERGE CASHWRAP PORTAL
B-6	WOOD BASE	L.T. CUSTOM FIXTURES	1/4" THICK 4" HIGH (SCRIBABLE) WOOD BASE (TRANSVERSE GRAIN) WITH QUIRK	UNIT 5B/5C, PASS THRU PORTAL, & CONCIERGE CASHWRAP PORTAL
	WALL COVERINGS			
T-1	CERAMIC TILE	DALTILE 800-365-8453	SEMI-GLOSS - "WHITE 0100" - 3" x 6" (FIELD TILE), 1/8" JOINTS	STANDARD TOILET ROOMS & BACKWALL AT DRINKING FOUNTAIN (BY G.C.)
T-3	CERAMIC TILE	DALTILE 800-365-8453	LINERS - "WHITE 0100" - 2" x 6" (CHAIR RAIL), 1/8" JOINTS	STANDARD TOILET ROOMS & BACKWALL AT DRINKING FOUNTAIN (BY G.C.)
T-5	CERAMIC TILE	DALTILE 800-365-8453	"DM 14 COBALT" - 1" X 6" (LINER BAR), 1/8" JOINTS	STANDARD TOILET ROOMS & BACK WALL AT DRINKING FOUNTAIN (BY G.C.)
T-6	TILE	WALKER ZANGER	VINTAGE GLASS "PEARL LUSTER" 1"x1" MOSAIC TILE	PASS THRU NICHE, DEMO SINK, 9 NICHE (BY OWNER)
~~T-7~~	~~TILE~~	~~ATLAS CONCORDE~~	~~STUDIO LINE A, 11 5/8" x 23 3/8", POLISHED, 00 WHITE, 1/8" JOINTS~~	~~ELEVATED RESTROOM WALLS (BY OWNER)~~
MT-2	METAL PANELS	LAMBERT	MATCH KAWNEER "INTERPON D2000 BONE WHITE"	STOREFRONT METAL PANELS
MT-3	METAL PANELS	LAMBERT	TO MATCH BENJAMIN MOORE HC-41 - "RICHMOND GOLD"	BASE & REVEAL AT STOREFRONT (PLANKING SIDE)
WD-3	WOOD	L.T. CUSTOM FIXTURES	FLAT CUT WHITE OAK WITH CLEAR FINISH	TRIMS / CABINETS/ STOREFRONT & PASS-THRU PORTAL
WD-W	WHITE TRIM	L.T. CUSTOM FIXTURES	PREFINISHED WHITE TRIM - VARIOUS PROFILES	TRIMS / CABINETS/ BACKWRAP SURROUNDS
WC-1	WALL COVERING	DREAMSCAPE	BLUE GINGHAM WALL COVERING	WALLS TO BE PRIMED, PAINTED PT-1 AND SIZING PRIMED PRIOR TO WALL COVERING INSTALLATION.
~~WC-3~~	~~WALL COVERING~~	~~RUGGLES~~	~~CUSTOM WALLGRAPHIC~~	~~ASSOCIATE BREAK AREA~~
	CEILING			
ACT-1	ACOUSTICAL CEILING TILE	ARMSTRONG	PANEL NO. 1774 - 2x2 - 24" TILE ON ARCHITECTURAL PRELUDE 15/16" XL EXPOSED TEE SUSPENSION SYSTEM	SALES AREA CEILINGS. TILE AND GRID TO BE WHITE.
ACT-2	ACOUSTICAL CEILING TILE	ARMSTRONG	CORTEGA NO. 761 - 24" x 48" NON-DIRECTIONAL FISSURED ON PRELUDE XL 15/16" EXPOSED TEE GRID	NON-RATED CORRIDOR CEILING. TILE AND GRID TO BE WHITE.
~~ACT-3~~	~~1 HR RATED CEILING TILE~~	~~ARMSTRONG~~	~~CIRRUS NO. 577 - 24" x 24" x 3/4" FIRE RESISTANT TILE ON SUPRAFINE 9/16" FIRE RESISTANT GRID.~~	~~SALES AREA CEILINGS. TILE AND GRID TO BE WHITE.~~
~~ACT-4~~	~~1 HR RATED CEILING TILE~~	~~ARMSTRONG~~	~~CORTEGA NO. 823 - 24" x 48" x 15/16" FIRE RESISTANT TILE ON FIRESAFE 15/16" GRID~~	~~RATED CORRIDOR CEILING. TILE AND GRID TO BE WHITE.~~
	GROUTS / SEALANTS			
S-2	ADHESIVE	G.E.	1200 SERIES SILICONE	FOR USE WITH MT-2 & MT-3 FOR STOREFRONT METAL INSTALLATION
S-4	WOOD SEALER	BID	WATER-BASE POLYURETHANE, CLEAR SATIN FINISH	NON-SALES WOOD SHELVES
S-5	GROUT	LATICRETE	NO. 44 - "BRIGHT WHITE"	FOR USE WITH T-1, T-3, T-5 & FC-20 (BY G.C.)
S-11	GROUT	HYDROMENT	NO. 1141 - "FLASH WALNUT"	FOR USE WITH FC-18 UNSANDED (BY G.C.)
S-12	GROUT	STARGLASS	NO. 600 - "DIAMOND"	FOR USE WITH T-6 (BY OWNER)
S-13	GROUT	HYDROMENT	NO. 1158 - "CLASSIC BONE"	FOR USE WITH FC-19 & T-7 (BY G.C.)
	GLASS			
~~G-2~~	~~DISPLAY GLASS~~	~~BID~~	~~1/4" CLEAR TEMPERED GLASS~~	~~OPERABLE DISPLAY WINDOW~~
~~G-3~~	~~INSULATED STOREFRONT GLASS~~	~~BID~~	~~1" CLEAR INSULATED TEMPERED GLASS~~	~~EXTERIOR STOREFRONT CONDITIONS, OF 5 UNLESS OTHERWISE NOTED~~
G-4	STOREFRONT GLASS	BID	1/2" CLEAR TEMPERED GLASS	AT STOREFRONT DISPLAY WINDOWS, FRAMELESS DOORS & SIDELITES (INTERIOR MALL LOCATION)
~~G-5~~	~~STOREFRONT GLASS~~	~~BID~~	~~3/4" CLEAR TEMPERED GLASS~~	~~AT STOREFRONT DISPLAY WINDOWS, FRAMELESS DOORS & SIDELITES (INTERIOR MALL LOCATION)~~
~~G-6~~	~~LAMINATED STOREFRONT GLASS~~	~~BID~~	~~9/16" CLEAR LAMINATED TEMPERED GLASS~~	~~EXTERIOR STOREFRONT CONDITIONS REQUIRING HURRICANE RESISTANCE~~
G-7	STOREFRONT GLASS	BID	1/2" STARPHIRE GLASS	AT STOREFRONT ILLUMINATED TRANSOM ABOVE ENTRANCE (INTERIOR MALL LOCATIONS WHEN G-8 IS NOT PERMITTED BY ENGINEER)
~~G-8~~	~~STOREFRONT FLEX~~	~~BID~~	~~1/2" CLEAR FLEX~~	~~AT STOREFRONT ILLUMINATED TRANSOM ABOVE ENTRANCE (INTERIOR MALL LOCATIONS WHENEVER APPLICABLE) COORDINATE WITH ENGINEER~~
~~G-9~~	~~INSULATED STOREFRONT GLASS~~	~~BID~~	~~1" STARPHIRE INSULATED GLASS~~	~~AT STOREFRONT ILLUMINATED TRANSOM ABOVE ENTRANCE (EXTERIOR MALL LOCATIONS)~~
~~G-11~~	~~STOREFRONT GLASS~~	~~ALL NEW GLASS~~	~~1" INSULATED NON-GLARE GLASS~~	~~EXTERIOR STOREFRONT CONDITIONS, G.C. TO COORDINATE SIZE WITH OWNER'S PURCHASING AGENT IN WEEK 12 OF CONSTRUCTION~~
G-12	POLYCARBONATE	DIGICO	1/2" POLYCARBONATE P